

Zoning Board of Appeals
c/o Mr. Zachary McBride, Chair
19 Washington Street, Sherborn, MA 01770

Re: 41 North Main Street | Limited Stormwater Report

Dear Members of the Zoning Board of Appeals,

On behalf of Barsky Estate Realty Trust, Highpoint Engineering Inc. submits this executive summary to update the Board on the stormwater management efforts for the proposed multifamily residential development at 41 North Main Street. Following a site visit and soil testing, we have prepared the attached report summarizing our findings and stormwater design.

The attached "Limited Stormwater Report" is intended to address DEP stormwater regulations regarding functionality and compliance. We believe the information provided is sufficient for your peer reviewer to evaluate the viability of the project's stormwater management design intent and strategy. Additional design and analysis will be completed and submitted prior to final approval.

Project Overview

The project includes five duplex homes and six triplex homes, with associated utilities, landscaping, and stormwater improvements. The stormwater design ensures compliance with state and local standards while addressing both environmental and community needs.

Stormwater Management Highlights

- Site Evaluation and Soil Testing:** On-site soil testing confirmed that the proposed infiltration systems are located in areas with suitable soil conditions, maintaining a minimum separation of four feet above seasonal high groundwater, ensuring effective recharge and groundwater protection.
- Peak Runoff Control:** Designed measures, including detention basins and infiltration systems, ensure post-development runoff rates remain below pre-development levels, protecting downstream areas.
- Water Quality Protection:** The system uses advanced treatment units to remove at least 80% of Total Suspended Solids (TSS), ensuring clean water discharge.
- Compliance:** The design meets or exceeds the Massachusetts Department of Environmental Protection's Stormwater Standards.

Key Benefits

- Reduced runoff impacts.
- Improved water quality.
- Compliance with local and state regulations.

The attached technical memo outlines these points in more detail and confirms that the project aligns with DEP's stormwater best practices and responsible site development. The work completed demonstrates our commitment to meeting regulatory requirements and supporting sustainable development in Sherborn. Please contact us at 781-770-0970 with any questions.

Respectfully,
HIGHPOINT

m. Fabbiano
Michael Fabbiano
Vice President

Cc. Paul Haverty Esq,
Lynne Sweet
Gary Barsky



LIMITED STORMWATER MANAGEMENT ANALYSIS

Proposed Multi-family Residential Development | 41 North Main Street | Sherborn, MA

Project Address:

41 North Main Street
Sherborn, MA 01770

Date Prepared:

December 6, 2024

Project Number:


23048

Prepared for:

Barsky Estate Realty Trust
23 Hunting Lane
Sherborn, MA 01770

Prepared by:

Highpoint Engineering Inc.
Dedham Executive Center
980 Washington Street, Suite 216
Dedham, MA 02026
www.highpointeng.com



INTRODUCTION

This analysis summarizes pre- and post-development stormwater impacts associated with the construction of a new multi-family residential development (the Project) located at 41 North Main Street and 6 Powderhouse Lane (the Subject Property) in Sherborn, Massachusetts. The Subject Property is shown on the Town of Sherborn Assessors' Map 11 as Parcel 0-41 and Map 11 as Parcel 0-43.

The land area of the Subject Property is approximately $7.24\pm$ acres. The Subject Property is located within Residence A (RA) and Business G (BG) Zoning Districts. The Subject Property is bounded by Hunting Lane to the north, North Main Street to the east, and abutting residential properties to the south and west. The Subject Property is currently accessed via four curb cuts, two off North Main Street, one off Hunting Lane, and one off Powderhouse Lane.

The Subject Property currently supports two dwellings, a barn, and a garage with a small parking lot and associated utilities.

Runoff from ground surfaces of the developed portion of the Subject Property flows in a predominantly westerly direction over land off property to an existing culvert that runs underneath Hunting Lane. Stormwater also flows in an east direction towards North Main Street where it enters the municipal drainage system. There are Bordering Vegetative Wetland areas located to the west of the site (offsite).

Work associated with the Project includes:

- Construction of (5) five duplex homes and (6) six triplex homes.
- Construction of landscape and hardscape improvements.
- Construction of stormwater management improvements, including catch basins, drain manholes, water quality units, surface infiltration basin, surface detention basin, rain garden and an underground detention system.
- Construction of utility infrastructure improvements, including new domestic water, new fire service, sewer, electrical/telecommunications to all proposed dwellings.

Disclaimer: This is a limited design and analysis intended solely to address state stormwater regulations related to functionality and compliance. The information provided is sufficient to evaluate the viability of the project's stormwater management design intent and strategy. We acknowledge that additional design and analysis will be required before final approval.

Massachusetts Stormwater Standards

STANDARD 1:

No New Untreated Discharges

All existing discharge points are maintained, and mitigation is proposed to treat discharge impacts at existing points as feasible.

STANDARD 2:

Peak Rate Attenuation

The increase in impervious areas due to the new development is mitigated via the implementation of a subsurface detention system, a surface detention basin, and a surface infiltration basin. Supplemental data can be seen below explaining how this is accomplished. The hydrologic model, analysis, and proposed mitigation measures have been developed using, Hydrologic modeling techniques and methods established in NRCS - Technical Releases No. 20 and No. 55 (TR-20 and TR-55) using proprietary HydroCAD stormwater modeling software and Massachusetts Department of Environmental Protection – Stormwater Handbook Volumes #1, #2, and #3 (as amended).

Rainfall Data

Peak stormwater discharge discharge rates have been determined for total rainfall estimated for the 2, 10, 25, and 100-year storm event recurrence intervals. For this analysis, the values used for the 24-year rainfall calculations were taken from the latest NOAA Atlas 14, Volume 10, Version 3 data for the subject property, and are outlined in Table 1 below.

Table 1. – Summary of Rainfall Data

Reference	Rainfall Recurrence Interval	24 Hour Rainfall Depth
NOAA Atlas 14 Volume 10 Version 3	2-Year Storm	3.35 inches
	10-Year Storm	5.24 inches
	25-Year Storm	6.42 inches
	100-Year Storm	8.23 inches

Table 2. – Summary of USDA Soil Classification

Soil Classification	Hydrologic Soil Group (HSG)
103D – Charlton-Hollis-Rock Outcrop Complex, 15 to 25 percent slopes	HSG A/D (Assumed B)
307B – Paxton Fine Sandy Loam, 0 to 8 percent slopes	HSG C
260B – Sudbury Fine Sandy Loam, 3 to 8 percent slopes	HSG B
626B – Merrimac-Urban Land Complex, 0 to 8 percent slopes	HSG A/D (Assumed A)
254A – Merrimac Fine Sandy Loam, 0 to 3 percent slopes	HSG A

Subsurface investigations comprising of 6 test pits were conducted within the proposed subsurface and both surface infiltration/detention basins by Highpoint Engineering, Inc. on November 20th, 2024. An infiltration rate of 1.02 is used based on test pit results.

Groundwater was only observed in 4 of the 6 test pits that were conducted. Groundwater depth ranges from 6.67' to 9' below existing grade. The proposed stormwater management systems intended for infiltration are designed with bottom depths at least 4 feet above the seasonal high groundwater (SHGW).

Table 3. – Summary of Pre- and Post-Development Peak Rates of Runoff

Design Storm	POA 1: Hunting Lane		
	Pre-Dev	Post-Dev	Change
2 Year	2.60 cfs	1.27 cfs	-1.33 cfs
10 Year	7.86 cfs	5.92 cfs	-1.94 cfs
25 Year	11.72 cfs	8.41 cfs	-3.31 cfs
100 Year	18.09 cfs	17.73 cfs	-0.36 cfs
Design Storm	POA 2: North Main Street		
	Pre-Dev	Post-Dev	Change
2 Year	1.22 cfs	0.75 cfs	-0.47 cfs
10 Year	3.23 cfs	1.79 cfs	-1.44 cfs
25 Year	4.64 cfs	2.50 cfs	-2.14 cfs
100 Year	6.92 cfs	3.63 cfs	-3.29 cfs
Design Storm	POA 3: 33 North Main Street		
	Pre-Dev	Post-Dev	Change
2 Year	0.25 cfs	0.03 cfs	-0.22 cfs
10 Year	0.97 cfs	0.37 cfs	-0.60 cfs
25 Year	1.50 cfs	0.71 cfs	-0.79 cfs
100 Year	2.41 cfs	1.32 cfs	-1.09 cfs

STANDARD 3:

Recharge

The required recharge volume for "B" soils is provided within the detention/infiltration basin below the lowest outlet invert elevation. Recharge volume calculations can be seen below.

The surface infiltration/detention system is proposed to completely drain within 72 hours. These calculations can be seen below.

Groundwater Recharge Calculations:

Review of the United States Department of Agricultural (USDA) Natural Resources Conservation Service (NRCS) indicates that the parent soils within the limit of Watersheds comprise of Hydrologic Soil Group A, B & C.

The Massachusetts Stormwater Handbook determines the required recharge volume using a calculation of 0.60 inches of runoff for "A" soils, 0.35 inches of runoff for "B" soils, and 0.25 inches of runoff for "C" soils multiplied by the total contributing impervious cover of the watersheds. Watershed PR WS-1A comprises of landscape/lawn areas, rooftop and pavement. Runoff from the watersheds flow to the surface infiltration/detention basin (IB-1) prior to discharging off-site.

A design infiltration rate of 1.02 inches per hour was conservatively used for the analysis based on the results of on-site soil testing performed on November 20th, 2024.

Mass DEP Requirement

$$\begin{aligned}\text{Required Recharge Volume} &= 0.60 \text{ inches} \times \text{Total Impervious Area for "A" soils} \\ &= 0.60 \text{ inches} \times 13,516 \text{ ft}^2 \times (1/12 \text{ in}/\text{ft}) = 676 \text{ ft}^3\end{aligned}$$

$$\begin{aligned} \text{Required Recharge Volume} &= 0.35 \text{ inches} \times \text{Total Impervious Area for "B" soils} \\ &= 0.35 \text{ inches} \times 70,935 \text{ ft}^2 \times (1/12 \text{ in}/\text{ft}) = 2,069 \text{ ft}^3 \end{aligned}$$

Required Recharge Volume = 0.25 inches x Total Impervious Area for "C" soils
= 0.25 inches x 3,300 ft² x (1/12 in/ft) = 69 ft³

Total Required Recharge Volume for Overall Project = 2,814 ft³

Recharge to Groundwater Provided

Volume Provided in IB-1 (Below elevation 173.00 ft) =9,794 ft³

The total recharge volume provided exceeds the minimum recharge requirement for all soils.

Total Recharge Volume Provided **9,794 ft³ > 2,814 ft³**

Drawdown Calculations:

Drawdown Time:

$$T = V / (K \cdot A)$$

where T = drawdown time (hours) V = volume below lowest outlet (ft^3) K = hydraulic conductivity (ft/hr)

$$= ([1.02 \text{ in/hr}] * (1 \text{ ft}/12 \text{ in}))$$

$$= 0.085 \text{ ft/hr}$$

 A = bottom area of infiltration system (ft^2)

[Surface Infiltration Basin -1]:

$$V = 9,794 \text{ ft}^3$$

$$K = 0.085 \text{ ft/hr}$$

$$A = 1,749 \text{ ft}^2$$

$$T = (9,794 \text{ ft}^3) / (0.201 \text{ ft/hr}) (1,749 \text{ ft}^2)$$

$$= 65.9 \text{ hours} < 72 \text{ hours}$$

STANDARD 4:

Water Quality

No Long-Term Pollution Prevention Plan is attached or submitted with these documents, but they will be submitted once a site plan review application is submitted.

Contech CDS proprietary hydrodynamic separator and infiltration BMP treatment trains have been sized to treat the full water quality and are designed to achieve 80% overall TSS removal. The 0.5" water quality volume is being used. Water quality calculations below can be seen below.

Water Quality Volume Calculations:

This analysis is to evaluate water quality volume criteria according to "Volume 1 Chapter 1: Stormwater Management Standards." The Project comprises of a surface infiltration basin to provide water quality for the new development.

Water Quality Volume Required:

(Watershed 1A)

Paved Impervious Area	= 59,117 ft ²
Water Quality Volume Requirement	= 0.5 inch over total impervious area
	= 59,117 ft ² x ([0.5]/12)
	= [2,463] ft ³

(Watershed 1B)

Paved Impervious Area	= 10,733 ft ²
Water Quality Volume Requirement	= 0.5 inch over total impervious area
	= 10,733 ft ² x ([0.5]/12)
	= [447] ft ³

(Watershed 1C)

Paved Impervious Area	= 2,798 ft ²
Water Quality Volume Requirement	= 0.5 inch over total impervious area
	= 2,798 ft ² x ([0.5]/12)
	= [116] ft ³

(Watershed 1D)

Paved Impervious Area	= 30,589 ft ²
Water Quality Volume Requirement	= 0.5 inch over total impervious area
	= 30,589 ft ² x ([0.5]/12)
	= [1,274] ft ³

(Watershed 1E)

Paved Impervious Area	= 12,887 ft ²
Water Quality Volume Requirement	= 0.5 inch over total impervious area
	= 12,887 ft ² x ([0.5]/12)
	= [537] ft ³

Water Quality Volume Provided in Infiltration BMPs:

(Watershed 1A, 1B, 1C, 1D, 1E)

[IB-1]: [Surface Infiltration Basin]

= Volume below elevation [173.00]'

= [9,794] ft³ [FROM HYDROCAD]

Total Volume Provided

= [9,794] ft³= **[9,794] ft³ > [4,837] ft³**

TSS Removal:

Treatment Train 1

B BMP ¹	C TSS Removal Rate ¹	D Starting TSS Load*	E Amount Removed (C*D)	F Remaining Load (D-E)
Sediment Forebay	0.25	1.00	0.25	0.75
Rain Garden	0.90	0.75	0.68	0.08
	0.00	0.08	0.00	0.08
	0.00	0.08	0.00	0.08
	0.00	0.08	0.00	0.08

Total TSS Removal =

93%

 Separate Form Needs to
be Completed for Each
Outlet or BMP Train

Treatment Train 2

B BMP ¹	C TSS Removal Rate ¹	D Starting TSS Load*	E Amount Removed (C*D)	F Remaining Load (D-E)
Deep Sump and Hooded Catch Basin	0.25	1.00	0.25	0.75
Proprietary Treatment Practice	0.50	0.75	0.38	0.38
Infiltration Basin	0.80	0.38	0.30	0.08
	0.00	0.08	0.00	0.08
	0.00	0.08	0.00	0.08

Total TSS Removal =

93%

 Separate Form Needs to
be Completed for Each
Outlet or BMP Train

Treatment Train 3

B BMP ¹	C TSS Removal Rate ¹	D Starting TSS Load*	E Amount Removed (C*D)	F Remaining Load (D-E)
Deep Sump and Hooded Catch Basin	0.25	1.00	0.25	0.75
Extended Dry Detention Basin	0.50	0.75	0.38	0.38
Proprietary Treatment Practice	0.50	0.38	0.19	0.19
	0.00	0.19	0.00	0.19
	0.00	0.19	0.00	0.19

Total TSS Removal =

81%

 Separate Form Needs to
be Completed for Each
Outlet or BMP Train

STANDARD 5:**Land Uses with Higher Potential Pollutant Loads (LUHPPLs)**

The proposed project is not a listed activity associated with a LUHPPL defined in the Handbook.

STANDARD 6:**Critical Areas**

The site does not discharge to a Critical Area.

STANDARD 7:**Redevelopments and Other Projects Subject to the Standards only to the Maximum Extent Practicable**

The proposed project is considered a new development. Stormwater management facilities and BMP designs are completed in full compliance with the Massachusetts Stormwater Management Standards in accordance with DEP guidance.

STANDARD 8:**Construction Period Pollution Prevention and Erosion and Sedimentation Control**

This project will be covered by a NPDES Construction General Permit and a SWPPP, but will be submitted with the final stormwater report and a hard copy shall be left on site throughout the duration of construction.

STANDARD 9:**Operation and Maintenance Plan**

No Post Construction Operation and Maintenance Plan is attached or submitted with these documents, but they will be provided with the final stormwater report.

STANDARD 10:

Prohibition of Illicit Discharges

No illicit discharge compliance state is attached or submitted with these documents, but they will be submitted prior to the discharge of any stormwater to post-construction BMPs.

CONCLUSION

The proposed residential development meets the minimum standards outlined in MassDEP stormwater requirements. Post-construction stormwater flows have been strategically designed to ensure that offsite discharge flow rates do not exceed preconstruction flow rates. The proposed stormwater management system addresses water quality, stormwater recharge, and flow attenuation through the implementation of infiltration/detention infrastructure and proprietary water quality units. These systems are designed to treat all impervious areas while reducing the overall volume of uncontrolled stormwater discharged offsite.

APPENDIX B – TEST PITS MAP



PROPOSED MULTI-FAMILY RESIDENTIAL DEVELOPMENT

41 NORTH MAIN STREET
SHERBORN, MA, 01770

OWNER/APPLICANT: BARKSY ESTATE REALTY TRUST

DEEP OBSERVATION HOLE LOG											
DEEP OBSERVATION HOLE NUMBER:			TP-1			GROUND ELEVATION:			171.50±		
Depth (in)	Horizon/ Layer	Matrix: Color-Moist	Redoximorphic Features			Texture (USDA)	Coarse Fragments (Percent by Volume)	Structure	Consistence (Moist)	Other	
			Depth (in)	Color	Percent						
0-15	Ap	10YR ½	N/A	N/A	N/A	SANDY LOAM	0	10-15	MASSIVE	FRIABLE	(1)
15-40	Bw	10YR ½	N/A	N/A	N/A	FINE SANE	0	0	SINGLE GRAIN	LOOSE	N/A
40-98	C	10YR ½	98	5YR ½ 5YR ½	>25	SANDY LOAM	20-30	20-30	MASSIVE	FRIABLE	(2)

NOTES:

1. LARGE ROCKS EMBEDDED AT SURFACE.
2. REDOX FEATURES OBSERVED AT BOTTOM OF EXCAVATION, EL.= 163.3±.
3. SOIL EVALUATED BY JOSEPH PECCIA (SE14774) ON NOVEMBER 21, 2024

DEEP OBSERVATION HOLE LOG											
DEEP OBSERVATION HOLE NUMBER:			TP-3			GROUND ELEVATION:			173.00±		
Depth (in)	Horizon/ Layer	Matrix: Color-Moist	Redoximorphic Features			Texture (USDA)	Coarse Fragments (Percent by Volume)	Structure	Consistence (Moist)	Other	
			Depth (in)	Color	Percent						
0-24	FILL	FILL	N/A	N/A	N/A	FILL	N/A	N/A	FILL	FILL	(1)
24-44	B	10YR ½	N/A	N/A	N/A	SANDY LOAM	5-10	10-20	MASSIVE	FRIABLE	N/A
44-108	C	10YR ½	108	5YR ½ 5YR ½	>25	SANDY LOAM	5-10	10-20	MASSIVE	FRIABLE	(2)

NOTES:

1. COMPACTED FILL MATERIAL USED FOR VEHICLE ACCESS.
2. REDOX FEATURES OBSERVED AT BOTTOM OF EXCAVATION, EL.= 164.0±.
3. SOIL EVALUATED BY JOSEPH PECCIA (SE14774) ON NOVEMBER 21, 2024

DEEP OBSERVATION HOLE LOG											
DEEP OBSERVATION HOLE NUMBER:			TP-5			GROUND ELEVATION:			179.00±		
Depth (in)	Horizon/ Layer	Matrix: Color-Moist	Redoximorphic Features			Texture (USDA)	Coarse Fragments (Percent by Volume)	Structure	Consistence (Moist)	Other	
			Depth (in)	Color	Percent						
0-10	Ap	10YR ½	N/A	N/A	N/A	SANDY LOAM	10-20	10-20	MASSIVE	FRIABLE	(1)
10-44	Bw	10YR ½	N/A	N/A	N/A	SANDY LOAM	10-20	30-40	MASSIVE	FRIABLE	(2)
44-78	C	10YR ½	N/A	N/A	N/A	SANDY LOAM	5-10	10-20	MASSIVE	FRIABLE	(3)

NOTES:

1. ROOTS AND BOULDERS EMBEDDED IN SURFACE.
2. LAYER EXTREMELY ROCKY.
3. REFUSAL DUE TO LARGE BOULDERS WITHIN EXCAVATION (20-30%). EL.=173.5±.
4. SOIL EVALUATED BY JOSEPH PECCIA (SE14774) ON NOVEMBER 21, 2024

DEEP OBSERVATION HOLE LOG											
DEEP OBSERVATION HOLE NUMBER:			TP-2			GROUND ELEVATION:			171.50±		
Depth (in)	Horizon/ Layer	Matrix: Color-Moist	Redoximorphic Features			Texture (USDA)	Coarse Fragments (Percent by Volume)	Structure	Consistence (Moist)	Other	
			Depth (in)	Color	Percent						
0-24	Ap	10YR ½	N/A	N/A	N/A	SANDY LOAM	0	0-5	MASSIVE	FRIABLE	(1)
24-53	Bw	FILL	N/A	N/A	N/A	FILL	N/A	N/A	FILL	FILL	(2)
53-80	C	10 YR ½	80	5YR ½ 5YR ½	>25	SANDY LOAM	0-5	0-5	MASSIVE	FRIABLE	(3)

NOTES:


1. ROOTS FOUND WITHIN SURFACE.
2. FILL MATERIAL INCLUDED GLASS PIECES, BRICKS ETC.
3. REDOX FEATURES OBSERVED AT BOTTOM OF EXCAVATION, EL.= 164.8±.
4. SOIL EVALUATED BY JOSEPH PECCIA (SE14774) ON NOVEMBER 21, 2024




DEEP OBSERVATION HOLE LOG											
DEEP OBSERVATION HOLE NUMBER:			TP-4			GROUND ELEVATION:			171.50±		
Depth (in)	Horizon/ Layer	Matrix: Color-Moist	Redoximorphic Features			Texture (USDA)	Coarse Fragments (Percent by Volume)	Structure	Consistence (Moist)	Other	
			Depth (in)	Color	Percent						
0-26	FILL	FILL	N/A	N/A	N/A	FILL	N/A	N/A	FILL	FILL	(1)
26-45	B	10YR ½	N/A	N/A	N/A	SANDY LOAM	10-30	10-15	MASSIVE	FRIABLE	(2)
45-84	C	10 YR ½	84	5YR ½	>25	SANDY LOAM	5-10	10-20	MASSIVE	FRIABLE	(3)

NOTES:

1. COMPACTED FILL MATERIAL USED FOR VEHICLE ACCESS.
2. LARGE ROCKS WITHIN LAYER (5%).
3. GREY MATERIAL AT BOTTOM OF EXCAVATION MOIST UPON TOUCH INDICATING REDOX. EL.= 164.5±
4. SOIL EVALUATED BY JOSEPH PECCIA (SE14774) ON NOVEMBER 21, 2024

WATERSHED MAPS





Routing Diagram for 23048_Pre-Dev

Prepared by Highpoint Engineering, Inc, Printed 12/6/2024
HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Area Listing (all nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
48,181	39	>75% Grass cover, Good, HSG A (EX-1, EX-3, EX-4)
61,350	61	>75% Grass cover, Good, HSG B (EX-1)
37,439	74	>75% Grass cover, Good, HSG C (EX-1, EX-3, EX-4)
15,249	82	Dirt roads, HSG B (EX-1)
2,900	85	Gravel roads, HSG B (EX-1)
46,663	79	Pasture/grassland/range, Poor, HSG B (EX-1)
1,534	98	Paved parking, HSG B (EX-4)
13,335	98	Paved parking, HSG C (EX-1, EX-3)
11,229	98	Roofs, HSG C (EX-1, EX-3)
19,411	55	Woods, Good, HSG B (EX-1, EX-2, EX-3)
32,724	70	Woods, Good, HSG C (EX-2, EX-3)
45,490	58	Woods/grass comb., Good, HSG B (EX-1, EX-3)
22,420	72	Woods/grass comb., Good, HSG C (EX-3)
357,925	66	TOTAL AREA

Soil Listing (all nodes)

Area (sq-ft)	Soil Group	Subcatchment Numbers
48,181	HSG A	EX-1, EX-3, EX-4
192,597	HSG B	EX-1, EX-2, EX-3, EX-4
117,147	HSG C	EX-1, EX-2, EX-3, EX-4
0	HSG D	
0	Other	
357,925		TOTAL AREA

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentEX-1: Existing Ws-1

Runoff Area=258,222 sf 8.34% Impervious Runoff Depth>0.64"
Flow Length=1,052' Tc=25.4 min CN=66 Runoff=2.55 cfs 13,723 cf

SubcatchmentEX-2: Existing Ws-2

Runoff Area=10,044 sf 0.00% Impervious Runoff Depth>0.41"
Flow Length=178' Tc=6.9 min CN=60 Runoff=0.08 cfs 343 cf

SubcatchmentEX-3: Existing Ws-3

Runoff Area=67,363 sf 4.50% Impervious Runoff Depth>0.83"
Flow Length=328' Tc=11.9 min CN=70 Runoff=1.22 cfs 4,645 cf

SubcatchmentEX-4: Existing Ws-4

Runoff Area=22,296 sf 6.88% Impervious Runoff Depth>0.48"
Flow Length=121' Tc=3.2 min CN=62 Runoff=0.25 cfs 898 cf

Link POA-1: Hunting Lane (Off-site)

Inflow=2.60 cfs 14,065 cf
Primary=2.60 cfs 14,065 cf

Link POA-2: North Main Street (Offsite)

Inflow=1.22 cfs 4,645 cf
Primary=1.22 cfs 4,645 cf

Link POA-3: 33 N Main Street (Offsite)

Inflow=0.25 cfs 898 cf
Primary=0.25 cfs 898 cf

**Total Runoff Area = 357,925 sf Runoff Volume = 19,608 cf Average Runoff Depth = 0.66"
92.71% Pervious = 331,827 sf 7.29% Impervious = 26,098 sf**


Summary for Subcatchment EX-1: Existing Ws-1

Runoff = 2.55 cfs @ 12.42 hrs, Volume= 13,723 cf, Depth> 0.64"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
37,653	39	>75% Grass cover, Good, HSG A
61,350	61	>75% Grass cover, Good, HSG B
21,649	74	>75% Grass cover, Good, HSG C
43,026	58	Woods/grass comb., Good, HSG B
8,196	55	Woods, Good, HSG B
15,249	82	Dirt roads, HSG B
46,663	79	Pasture/grassland/range, Poor, HSG B
2,900	85	Gravel roads, HSG B
8,520	98	Roofs, HSG C
13,016	98	Paved parking, HSG C
258,222	66	Weighted Average
236,686		91.66% Pervious Area
21,536		8.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
3.4	424	0.0900	2.10		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
0.4	62	0.0150	2.49		Shallow Concentrated Flow, C-D Paved Kv= 20.3 fps
3.2	133	0.0100	0.70		Shallow Concentrated Flow, D-E Short Grass Pasture Kv= 7.0 fps
9.1	383	0.0100	0.70		Shallow Concentrated Flow, E-F Short Grass Pasture Kv= 7.0 fps
25.4	1,052	Total			

Subcatchment EX-1: Existing Ws-1

Summary for Subcatchment EX-2: Existing Ws-2

Runoff = 0.08 cfs @ 12.15 hrs, Volume= 343 cf, Depth> 0.41"
 Routed to Link POA-1 : Hunting Lane (Off-site)


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
6,768	55	Woods, Good, HSG B
3,276	70	Woods, Good, HSG C
10,044	60	Weighted Average
10,044		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.1100	0.13		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
0.7	128	0.2100	3.21		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
6.9	178				Total

Subcatchment EX-2: Existing Ws-2

Hydrograph




Summary for Subcatchment EX-3: Existing Ws-3

Runoff = 1.22 cfs @ 12.19 hrs, Volume= 4,645 cf, Depth> 0.83"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description			
1,623	39	>75% Grass cover, Good, HSG A			
3,933	74	>75% Grass cover, Good, HSG C			
2,464	58	Woods/grass comb., Good, HSG B			
22,420	72	Woods/grass comb., Good, HSG C			
4,447	55	Woods, Good, HSG B			
29,448	70	Woods, Good, HSG C			
2,709	98	Roofs, HSG C			
319	98	Paved parking, HSG C			
67,363	70	Weighted Average			
64,335		95.50% Pervious Area			
3,028		4.50% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
2.6	278	0.0650	1.78		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
11.9	328	Total			

Subcatchment EX-3: Existing Ws-3


Summary for Subcatchment EX-4: Existing Ws-4

Runoff = 0.25 cfs @ 12.07 hrs, Volume= 898 cf, Depth> 0.48"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description		
8,905	39	>75% Grass cover, Good, HSG A		
11,857	74	>75% Grass cover, Good, HSG C		
1,534	98	Paved parking, HSG B		
22,296	62	Weighted Average		
20,762		93.12% Pervious Area		
1,534		6.88% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
0.3	21	0.0300	1.21	Sheet Flow, A-B Smooth surfaces n= 0.011 P2= 3.35"
2.0	29	0.0850	0.24	Sheet Flow, B-C Grass: Short n= 0.150 P2= 3.35"
0.9	71	0.0350	1.31	Shallow Concentrated Flow, C-D Short Grass Pasture Kv= 7.0 fps
3.2	121			Total


Subcatchment EX-4: Existing Ws-4



Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 268,266 sf, 8.03% Impervious, Inflow Depth > 0.63" for 2-YR event
Inflow = 2.60 cfs @ 12.42 hrs, Volume= 14,065 cf
Primary = 2.60 cfs @ 12.42 hrs, Volume= 14,065 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs


Link POA-1: Hunting Lane (Off-site)

Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 67,363 sf, 4.50% Impervious, Inflow Depth > 0.83" for 2-YR event
 Inflow = 1.22 cfs @ 12.19 hrs, Volume= 4,645 cf
 Primary = 1.22 cfs @ 12.19 hrs, Volume= 4,645 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs


Link POA-2: North Main Street (Offsite)



Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 22,296 sf, 6.88% Impervious, Inflow Depth > 0.48" for 2-YR event
Inflow = 0.25 cfs @ 12.07 hrs, Volume= 898 cf
Primary = 0.25 cfs @ 12.07 hrs, Volume= 898 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentEX-1: Existing Ws-1

Runoff Area=258,222 sf 8.34% Impervious Runoff Depth>1.72"
Flow Length=1,052' Tc=25.4 min CN=66 Runoff=7.69 cfs 37,016 cf

SubcatchmentEX-2: Existing Ws-2

Runoff Area=10,044 sf 0.00% Impervious Runoff Depth>1.31"
Flow Length=178' Tc=6.9 min CN=60 Runoff=0.34 cfs 1,093 cf

SubcatchmentEX-3: Existing Ws-3

Runoff Area=67,363 sf 4.50% Impervious Runoff Depth>2.04"
Flow Length=328' Tc=11.9 min CN=70 Runoff=3.23 cfs 11,447 cf

SubcatchmentEX-4: Existing Ws-4

Runoff Area=22,296 sf 6.88% Impervious Runoff Depth>1.45"
Flow Length=121' Tc=3.2 min CN=62 Runoff=0.97 cfs 2,687 cf

Link POA-1: Hunting Lane (Off-site)

Inflow=7.86 cfs 38,109 cf
Primary=7.86 cfs 38,109 cf

Link POA-2: North Main Street (Offsite)

Inflow=3.23 cfs 11,447 cf
Primary=3.23 cfs 11,447 cf

Link POA-3: 33 N Main Street (Offsite)

Inflow=0.97 cfs 2,687 cf
Primary=0.97 cfs 2,687 cf

Total Runoff Area = 357,925 sf Runoff Volume = 52,243 cf Average Runoff Depth = 1.75"
92.71% Pervious = 331,827 sf 7.29% Impervious = 26,098 sf


Summary for Subcatchment EX-1: Existing Ws-1

Runoff = 7.69 cfs @ 12.38 hrs, Volume= 37,016 cf, Depth> 1.72"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description
37,653	39	>75% Grass cover, Good, HSG A
61,350	61	>75% Grass cover, Good, HSG B
21,649	74	>75% Grass cover, Good, HSG C
43,026	58	Woods/grass comb., Good, HSG B
8,196	55	Woods, Good, HSG B
15,249	82	Dirt roads, HSG B
46,663	79	Pasture/grassland/range, Poor, HSG B
2,900	85	Gravel roads, HSG B
8,520	98	Roofs, HSG C
13,016	98	Paved parking, HSG C
258,222	66	Weighted Average
236,686		91.66% Pervious Area
21,536		8.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
3.4	424	0.0900	2.10		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
0.4	62	0.0150	2.49		Shallow Concentrated Flow, C-D Paved Kv= 20.3 fps
3.2	133	0.0100	0.70		Shallow Concentrated Flow, D-E Short Grass Pasture Kv= 7.0 fps
9.1	383	0.0100	0.70		Shallow Concentrated Flow, E-F Short Grass Pasture Kv= 7.0 fps
25.4	1,052	Total			

Subcatchment EX-1: Existing Ws-1

Summary for Subcatchment EX-2: Existing Ws-2

Runoff = 0.34 cfs @ 12.11 hrs, Volume= 1,093 cf, Depth> 1.31"
 Routed to Link POA-1 : Hunting Lane (Off-site)


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description
6,768	55	Woods, Good, HSG B
3,276	70	Woods, Good, HSG C
10,044	60	Weighted Average
10,044		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.1100	0.13		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
0.7	128	0.2100	3.21		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
6.9	178	Total			

Subcatchment EX-2: Existing Ws-2

Hydrograph




Summary for Subcatchment EX-3: Existing Ws-3

Runoff = 3.23 cfs @ 12.17 hrs, Volume= 11,447 cf, Depth> 2.04"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description			
1,623	39	>75% Grass cover, Good, HSG A			
3,933	74	>75% Grass cover, Good, HSG C			
2,464	58	Woods/grass comb., Good, HSG B			
22,420	72	Woods/grass comb., Good, HSG C			
4,447	55	Woods, Good, HSG B			
29,448	70	Woods, Good, HSG C			
2,709	98	Roofs, HSG C			
319	98	Paved parking, HSG C			
67,363	70	Weighted Average			
64,335		95.50% Pervious Area			
3,028		4.50% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
2.6	278	0.0650	1.78		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
11.9	328	Total			

Subcatchment EX-3: Existing Ws-3


Summary for Subcatchment EX-4: Existing Ws-4

Runoff = 0.97 cfs @ 12.06 hrs, Volume= 2,687 cf, Depth> 1.45"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description		
8,905	39	>75% Grass cover, Good, HSG A		
11,857	74	>75% Grass cover, Good, HSG C		
1,534	98	Paved parking, HSG B		
22,296	62	Weighted Average		
20,762		93.12% Pervious Area		
1,534		6.88% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
0.3	21	0.0300	1.21	Sheet Flow, A-B Smooth surfaces n= 0.011 P2= 3.35"
2.0	29	0.0850	0.24	Sheet Flow, B-C Grass: Short n= 0.150 P2= 3.35"
0.9	71	0.0350	1.31	Shallow Concentrated Flow, C-D Short Grass Pasture Kv= 7.0 fps
3.2	121			Total


Subcatchment EX-4: Existing Ws-4



Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 268,266 sf, 8.03% Impervious, Inflow Depth > 1.70" for 10-YR event
Inflow = 7.86 cfs @ 12.37 hrs, Volume= 38,109 cf
Primary = 7.86 cfs @ 12.37 hrs, Volume= 38,109 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs


Link POA-1: Hunting Lane (Off-site)

Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 67,363 sf, 4.50% Impervious, Inflow Depth > 2.04" for 10-YR event
 Inflow = 3.23 cfs @ 12.17 hrs, Volume= 11,447 cf
 Primary = 3.23 cfs @ 12.17 hrs, Volume= 11,447 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs


Link POA-2: North Main Street (Offsite)



Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 22,296 sf, 6.88% Impervious, Inflow Depth > 1.45" for 10-YR event
Inflow = 0.97 cfs @ 12.06 hrs, Volume= 2,687 cf
Primary = 0.97 cfs @ 12.06 hrs, Volume= 2,687 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentEX-1: Existing Ws-1 Runoff Area=258,222 sf 8.34% Impervious Runoff Depth>2.52"
Flow Length=1,052' Tc=25.4 min CN=66 Runoff=11.47 cfs 54,309 cf

SubcatchmentEX-2: Existing Ws-2 Runoff Area=10,044 sf 0.00% Impervious Runoff Depth>2.01"
Flow Length=178' Tc=6.9 min CN=60 Runoff=0.55 cfs 1,684 cf

SubcatchmentEX-3: Existing Ws-3 Runoff Area=67,363 sf 4.50% Impervious Runoff Depth>2.91"
Flow Length=328' Tc=11.9 min CN=70 Runoff=4.64 cfs 16,331 cf

SubcatchmentEX-4: Existing Ws-4 Runoff Area=22,296 sf 6.88% Impervious Runoff Depth>2.19"
Flow Length=121' Tc=3.2 min CN=62 Runoff=1.50 cfs 4,066 cf

Link POA-1: Hunting Lane (Off-site) Inflow=11.72 cfs 55,993 cf
Primary=11.72 cfs 55,993 cf

Link POA-2: North Main Street (Offsite) Inflow=4.64 cfs 16,331 cf
Primary=4.64 cfs 16,331 cf

Link POA-3: 33 N Main Street (Offsite) Inflow=1.50 cfs 4,066 cf
Primary=1.50 cfs 4,066 cf

Total Runoff Area = 357,925 sf Runoff Volume = 76,389 cf Average Runoff Depth = 2.56"
92.71% Pervious = 331,827 sf 7.29% Impervious = 26,098 sf


Summary for Subcatchment EX-1: Existing Ws-1

Runoff = 11.47 cfs @ 12.37 hrs, Volume= 54,309 cf, Depth> 2.52"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description
37,653	39	>75% Grass cover, Good, HSG A
61,350	61	>75% Grass cover, Good, HSG B
21,649	74	>75% Grass cover, Good, HSG C
43,026	58	Woods/grass comb., Good, HSG B
8,196	55	Woods, Good, HSG B
15,249	82	Dirt roads, HSG B
46,663	79	Pasture/grassland/range, Poor, HSG B
2,900	85	Gravel roads, HSG B
8,520	98	Roofs, HSG C
13,016	98	Paved parking, HSG C
258,222	66	Weighted Average
236,686		91.66% Pervious Area
21,536		8.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
3.4	424	0.0900	2.10		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
0.4	62	0.0150	2.49		Shallow Concentrated Flow, C-D Paved Kv= 20.3 fps
3.2	133	0.0100	0.70		Shallow Concentrated Flow, D-E Short Grass Pasture Kv= 7.0 fps
9.1	383	0.0100	0.70		Shallow Concentrated Flow, E-F Short Grass Pasture Kv= 7.0 fps
25.4	1,052	Total			

Subcatchment EX-1: Existing Ws-1

Summary for Subcatchment EX-2: Existing Ws-2

Runoff = 0.55 cfs @ 12.11 hrs, Volume= 1,684 cf, Depth> 2.01"
 Routed to Link POA-1 : Hunting Lane (Off-site)


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description
6,768	55	Woods, Good, HSG B
3,276	70	Woods, Good, HSG C
10,044	60	Weighted Average
10,044		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.1100	0.13		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
0.7	128	0.2100	3.21		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
6.9	178				Total

Subcatchment EX-2: Existing Ws-2

Hydrograph



23048_Pre-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Existing Condition

Type III 24-hr 25-YR Rainfall=6.42"

Printed 12/6/2024


Page 28

Summary for Subcatchment EX-3: Existing Ws-3

Runoff = 4.64 cfs @ 12.17 hrs, Volume= 16,331 cf, Depth> 2.91"
Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description			
1,623	39	>75% Grass cover, Good, HSG A			
3,933	74	>75% Grass cover, Good, HSG C			
2,464	58	Woods/grass comb., Good, HSG B			
22,420	72	Woods/grass comb., Good, HSG C			
4,447	55	Woods, Good, HSG B			
29,448	70	Woods, Good, HSG C			
2,709	98	Roofs, HSG C			
319	98	Paved parking, HSG C			
67,363	70	Weighted Average			
64,335		95.50% Pervious Area			
3,028		4.50% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
2.6	278	0.0650	1.78		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
11.9	328	Total			

Subcatchment EX-3: Existing Ws-3


Summary for Subcatchment EX-4: Existing Ws-4

Runoff = 1.50 cfs @ 12.06 hrs, Volume= 4,066 cf, Depth> 2.19"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description		
8,905	39	>75% Grass cover, Good, HSG A		
11,857	74	>75% Grass cover, Good, HSG C		
1,534	98	Paved parking, HSG B		
22,296	62	Weighted Average		
20,762		93.12% Pervious Area		
1,534		6.88% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
0.3	21	0.0300	1.21	Sheet Flow, A-B Smooth surfaces n= 0.011 P2= 3.35"
2.0	29	0.0850	0.24	Sheet Flow, B-C Grass: Short n= 0.150 P2= 3.35"
0.9	71	0.0350	1.31	Shallow Concentrated Flow, C-D Short Grass Pasture Kv= 7.0 fps
3.2	121			Total

Subcatchment EX-4: Existing Ws-4



Summary for Link POA-1: Hunting Lane (Off-site)


Inflow Area = 268,266 sf, 8.03% Impervious, Inflow Depth > 2.50" for 25-YR event

Inflow = 11.72 cfs @ 12.36 hrs, Volume= 55,993 cf

Primary = 11.72 cfs @ 12.36 hrs, Volume= 55,993 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-1: Hunting Lane (Off-site)




Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 67,363 sf, 4.50% Impervious, Inflow Depth > 2.91" for 25-YR event

Inflow = 4.64 cfs @ 12.17 hrs, Volume= 16,331 cf

Primary = 4.64 cfs @ 12.17 hrs, Volume= 16,331 cf, Atten= 0%, Lag= 0.0 min


Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-2: North Main Street (Offsite)

Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 22,296 sf, 6.88% Impervious, Inflow Depth > 2.19" for 25-YR event
Inflow = 1.50 cfs @ 12.06 hrs, Volume= 4,066 cf
Primary = 1.50 cfs @ 12.06 hrs, Volume= 4,066 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentEX-1: Existing Ws-1 Runoff Area=258,222 sf 8.34% Impervious Runoff Depth>3.87"
Flow Length=1,052' Tc=25.4 min CN=66 Runoff=17.69 cfs 83,350 cf

SubcatchmentEX-2: Existing Ws-2 Runoff Area=10,044 sf 0.00% Impervious Runoff Depth>3.23"
Flow Length=178' Tc=6.9 min CN=60 Runoff=0.90 cfs 2,707 cf

SubcatchmentEX-3: Existing Ws-3 Runoff Area=67,363 sf 4.50% Impervious Runoff Depth>4.34"
Flow Length=328' Tc=11.9 min CN=70 Runoff=6.92 cfs 24,381 cf

SubcatchmentEX-4: Existing Ws-4 Runoff Area=22,296 sf 6.88% Impervious Runoff Depth>3.46"
Flow Length=121' Tc=3.2 min CN=62 Runoff=2.41 cfs 6,426 cf

Link POA-1: Hunting Lane (Off-site) Inflow=18.09 cfs 86,057 cf
Primary=18.09 cfs 86,057 cf

Link POA-2: North Main Street (Offsite) Inflow=6.92 cfs 24,381 cf
Primary=6.92 cfs 24,381 cf

Link POA-3: 33 N Main Street (Offsite) Inflow=2.41 cfs 6,426 cf
Primary=2.41 cfs 6,426 cf

Total Runoff Area = 357,925 sf Runoff Volume = 116,864 cf Average Runoff Depth = 3.92"
92.71% Pervious = 331,827 sf 7.29% Impervious = 26,098 sf


Summary for Subcatchment EX-1: Existing Ws-1

Runoff = 17.69 cfs @ 12.36 hrs, Volume= 83,350 cf, Depth> 3.87"
Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description
37,653	39	>75% Grass cover, Good, HSG A
61,350	61	>75% Grass cover, Good, HSG B
21,649	74	>75% Grass cover, Good, HSG C
43,026	58	Woods/grass comb., Good, HSG B
8,196	55	Woods, Good, HSG B
15,249	82	Dirt roads, HSG B
46,663	79	Pasture/grassland/range, Poor, HSG B
2,900	85	Gravel roads, HSG B
8,520	98	Roofs, HSG C
13,016	98	Paved parking, HSG C
258,222	66	Weighted Average
236,686		91.66% Pervious Area
21,536		8.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.3	50	0.0400	0.09		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
3.4	424	0.0900	2.10		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
0.4	62	0.0150	2.49		Shallow Concentrated Flow, C-D Paved Kv= 20.3 fps
3.2	133	0.0100	0.70		Shallow Concentrated Flow, D-E Short Grass Pasture Kv= 7.0 fps
9.1	383	0.0100	0.70		Shallow Concentrated Flow, E-F Short Grass Pasture Kv= 7.0 fps
25.4	1,052	Total			

Subcatchment EX-1: Existing Ws-1

Summary for Subcatchment EX-2: Existing Ws-2

Runoff = 0.90 cfs @ 12.11 hrs, Volume= 2,707 cf, Depth> 3.23"
 Routed to Link POA-1 : Hunting Lane (Off-site)


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description
6,768	55	Woods, Good, HSG B
3,276	70	Woods, Good, HSG C
10,044	60	Weighted Average
10,044		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.1100	0.13		Sheet Flow, A-B Grass: Bermuda n= 0.410 P2= 3.35"
0.7	128	0.2100	3.21		Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps
6.9	178	Total			

Subcatchment EX-2: Existing Ws-2

Hydrograph




Summary for Subcatchment EX-3: Existing Ws-3

Runoff = 6.92 cfs @ 12.17 hrs, Volume= 24,381 cf, Depth> 4.34"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description
1,623	39	>75% Grass cover, Good, HSG A
3,933	74	>75% Grass cover, Good, HSG C
2,464	58	Woods/grass comb., Good, HSG B
22,420	72	Woods/grass comb., Good, HSG C
4,447	55	Woods, Good, HSG B
29,448	70	Woods, Good, HSG C
2,709	98	Roofs, HSG C
319	98	Paved parking, HSG C
67,363	70	Weighted Average
64,335		95.50% Pervious Area
3,028		4.50% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft)
9.3	50	0.0400
2.6	278	0.0650
11.9	328	Total
Velocity (ft/sec)	Capacity (cfs)	Description
0.09		Sheet Flow, A-B
		Grass: Bermuda n= 0.410 P2= 3.35"
1.78		Shallow Concentrated Flow, B-C
		Short Grass Pasture Kv= 7.0 fps

Subcatchment EX-3: Existing Ws-3


Summary for Subcatchment EX-4: Existing Ws-4

Runoff = 2.41 cfs @ 12.05 hrs, Volume= 6,426 cf, Depth> 3.46"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description		
8,905	39	>75% Grass cover, Good, HSG A		
11,857	74	>75% Grass cover, Good, HSG C		
1,534	98	Paved parking, HSG B		
22,296	62	Weighted Average		
20,762		93.12% Pervious Area		
1,534		6.88% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
0.3	21	0.0300	1.21	Sheet Flow, A-B Smooth surfaces n= 0.011 P2= 3.35"
2.0	29	0.0850	0.24	Sheet Flow, B-C Grass: Short n= 0.150 P2= 3.35"
0.9	71	0.0350	1.31	Shallow Concentrated Flow, C-D Short Grass Pasture Kv= 7.0 fps
3.2	121			Total

Subcatchment EX-4: Existing Ws-4




Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 268,266 sf, 8.03% Impervious, Inflow Depth > 3.85" for 100-YR event

Inflow = 18.09 cfs @ 12.36 hrs, Volume= 86,057 cf

Primary = 18.09 cfs @ 12.36 hrs, Volume= 86,057 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-1: Hunting Lane (Off-site)

Summary for Link POA-2: North Main Street (Offsite)


Inflow Area = 67,363 sf, 4.50% Impervious, Inflow Depth > 4.34" for 100-YR event

Inflow = 6.92 cfs @ 12.17 hrs, Volume= 24,381 cf

Primary = 6.92 cfs @ 12.17 hrs, Volume= 24,381 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-2: North Main Street (Offsite)




Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 22,296 sf, 6.88% Impervious, Inflow Depth > 3.46" for 100-YR event


Inflow = 2.41 cfs @ 12.05 hrs, Volume= 6,426 cf

Primary = 2.41 cfs @ 12.05 hrs, Volume= 6,426 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

APPENDIX A – PRE AND POST HYDROLOGIC CALCULATIONS



23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Printed 12/6/2024

Page 2

Area Listing (all nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
44,552	39	>75% Grass cover, Good, HSG A (1S, 7S, 8S, 10S, 11S)
129,567	61	>75% Grass cover, Good, HSG B (1S, 8S, 11S, 17S, 23S)
66,042	74	>75% Grass cover, Good, HSG C (1S, 10S, 17S, 23S)
13,516	98	Unconnected pavement, HSG A (1S, 7S, 10S)
70,935	98	Unconnected pavement, HSG B (1S, 8S, 10S, 17S, 23S)
33,300	98	Unconnected pavement, HSG C (1S, 17S)
357,912	73	TOTAL AREA

23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Printed 12/6/2024

Page 3

Soil Listing (all nodes)

Area (sq-ft)	Soil Group	Subcatchment Numbers
58,068	HSG A	1S, 7S, 8S, 10S, 11S
200,502	HSG B	1S, 8S, 10S, 11S, 17S, 23S
99,342	HSG C	1S, 10S, 17S, 23S
0	HSG D	
0	Other	
357,912		TOTAL AREA

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1S: Proposed WS-1A	Runoff Area=127,763 sf 45.93% Impervious Runoff Depth>1.40" Tc=6.0 min CN=80 Runoff=5.09 cfs 14,951 cf
Subcatchment7S: Proposed WS-1B	Runoff Area=25,142 sf 42.69% Impervious Runoff Depth>0.56" Tc=6.0 min CN=64 Runoff=0.33 cfs 1,174 cf
Subcatchment8S: Proposed WS-1C	Runoff Area=62,999 sf 5.13% Impervious Runoff Depth>0.25" Flow Length=970' Tc=37.8 min UI Adjusted CN=55 Runoff=0.13 cfs 1,287 cf
Subcatchment10S: Proposed WS-3	Runoff Area=27,552 sf 5.91% Impervious Runoff Depth>0.98" Tc=6.0 min UI Adjusted CN=73 Runoff=0.75 cfs 2,261 cf
Subcatchment11S: Proposed WS-4	Runoff Area=20,492 sf 0.00% Impervious Runoff Depth>0.17" Flow Length=195' Tc=6.4 min CN=52 Runoff=0.03 cfs 297 cf
Subcatchment17S: Proposed WS-1D	Runoff Area=54,797 sf 52.55% Impervious Runoff Depth>1.61" Tc=6.0 min CN=83 Runoff=2.51 cfs 7,359 cf
Subcatchment23S: Proposed WS-1E	Runoff Area=39,167 sf 37.48% Impervious Runoff Depth>1.15" Tc=6.0 min CN=76 Runoff=1.27 cfs 3,767 cf
Pond DB-1: Det Basin	Peak Elev=176.69' Storage=4,261 cf Inflow=2.51 cfs 7,359 cf Outflow=0.30 cfs 3,456 cf
Pond IB-1: Infil Basin Discarded=0.09 cfs 2,757 cf Primary=0.00 cfs 0 cf Secondary=0.00 cfs 0 cf	Peak Elev=172.18' Storage=6,124 cf Inflow=3.30 cfs 8,872 cf Outflow=0.09 cfs 2,757 cf
Pond RG-1: Rain Garden	Peak Elev=171.53' Storage=1,173 cf Inflow=0.33 cfs 1,174 cf Outflow=0.00 cfs 0 cf
Pond UDS-1: Cultec 330 XLHD 15.0" Round Culvert x 4.00 n=0.012 L=15.0' S=0.0000 '/'	Peak Elev=172.18' Storage=0.140 af Inflow=5.09 cfs 14,951 cf Outflow=3.30 cfs 8,872 cf
Link POA-1: Hunting Lane (Off-site)	Inflow=1.27 cfs 8,510 cf Primary=1.27 cfs 8,510 cf
Link POA-2: North Main Street (Offsite)	Inflow=0.75 cfs 2,261 cf Primary=0.75 cfs 2,261 cf
Link POA-3: 33 N Main Street (Offsite)	Inflow=0.03 cfs 297 cf Primary=0.03 cfs 297 cf

Total Runoff Area = 357,912 sf Runoff Volume = 31,096 cf Average Runoff Depth = 1.04"
67.10% Pervious = 240,161 sf 32.90% Impervious = 117,751 sf

Summary for Subcatchment 1S: Proposed WS-1A


Runoff = 5.09 cfs @ 12.10 hrs, Volume= 14,951 cf, Depth> 1.40"
 Routed to Pond UDS-1 : Cultec 330 XLHD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
2,745	98	Unconnected pavement, HSG A
33,953	98	Unconnected pavement, HSG B
21,986	98	Unconnected pavement, HSG C
1,946	39	>75% Grass cover, Good, HSG A
41,046	61	>75% Grass cover, Good, HSG B
26,087	74	>75% Grass cover, Good, HSG C
127,763	80	Weighted Average
69,079		54.07% Pervious Area
58,684		45.93% Impervious Area
58,684		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 1S: Proposed WS-1A



Summary for Subcatchment 7S: Proposed WS-1B


Runoff = 0.33 cfs @ 12.11 hrs, Volume= 1,174 cf, Depth> 0.56"
 Routed to Pond RG-1 : Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
10,733	98	Unconnected pavement, HSG A
0	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
14,409	39	>75% Grass cover, Good, HSG A
0	61	>75% Grass cover, Good, HSG B
0	74	>75% Grass cover, Good, HSG C
25,142	64	Weighted Average
14,409		57.31% Pervious Area
10,733		42.69% Impervious Area
10,733		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 7S: Proposed WS-1B




Summary for Subcatchment 8S: Proposed WS-1C

Runoff = 0.13 cfs @ 12.77 hrs, Volume= 1,287 cf, Depth> 0.25"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Adj	Description
0	98		Unconnected pavement, HSG A
3,231	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
18,478	39		>75% Grass cover, Good, HSG A
41,290	61		>75% Grass cover, Good, HSG B
0	74		>75% Grass cover, Good, HSG C
62,999	56	55	Weighted Average, UI Adjusted
59,768			94.87% Pervious Area
3,231			5.13% Impervious Area
3,231			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
10.6	50	0.0100	0.08
27.2	920	0.0065	0.56
37.8	970	Total	
			Sheet Flow, Grass: Dense n= 0.240 P2= 3.35" Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps

Subcatchment 8S: Proposed WS-1C


Summary for Subcatchment 10S: Proposed WS-3

Runoff = 0.75 cfs @ 12.10 hrs, Volume= 2,261 cf, Depth> 0.98"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Adj	Description
38	98		Unconnected pavement, HSG A
1,589	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
1,223	39		>75% Grass cover, Good, HSG A
0	61		>75% Grass cover, Good, HSG B
24,702	74		>75% Grass cover, Good, HSG C
27,552	74	73	Weighted Average, UI Adjusted
25,925			94.09% Pervious Area
1,627			5.91% Impervious Area
1,627			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
Capacity (cfs)			Description
6.0			Direct Entry,

Subcatchment 10S: Proposed WS-3



23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Proposed Condition
Type III 24-hr 2-YR Rainfall=3.35"
 Printed 12/6/2024
 Page 10


Summary for Subcatchment 11S: Proposed WS-4

Runoff = 0.03 cfs @ 12.39 hrs, Volume= 297 cf, Depth> 0.17"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
0	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
8,496	39	>75% Grass cover, Good, HSG A
11,996	61	>75% Grass cover, Good, HSG B
0	74	>75% Grass cover, Good, HSG C
20,492	52	Weighted Average
20,492		100.00% Pervious Area
Tc	Length (feet)	Slope (ft/ft)
4.9	50	0.0700
1.5	145	0.0520
6.4	195	Total
Velocity (ft/sec)	Capacity (cfs)	Description
0.17		Sheet Flow, Grass: Dense n= 0.240 P2= 3.35"
1.60		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps

Subcatchment 11S: Proposed WS-4



Summary for Subcatchment 17S: Proposed WS-1D


Runoff = 2.51 cfs @ 12.09 hrs, Volume= 7,359 cf, Depth> 1.61"
 Routed to Pond DB-1 : Det Basin

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
17,482	98	Unconnected pavement, HSG B
11,314	98	Unconnected pavement, HSG C
0	39	>75% Grass cover, Good, HSG A
13,949	61	>75% Grass cover, Good, HSG B
12,052	74	>75% Grass cover, Good, HSG C
54,797	83	Weighted Average
26,001		47.45% Pervious Area
28,796		52.55% Impervious Area
28,796		100.00% Unconnected

Tc	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 17S: Proposed WS-1D



Summary for Subcatchment 23S: Proposed WS-1E


Runoff = 1.27 cfs @ 12.10 hrs, Volume= 3,767 cf, Depth> 1.15"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 2-YR Rainfall=3.35"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
14,680	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
0	39	>75% Grass cover, Good, HSG A
21,286	61	>75% Grass cover, Good, HSG B
3,201	74	>75% Grass cover, Good, HSG C
39,167	76	Weighted Average
24,487		62.52% Pervious Area
14,680		37.48% Impervious Area
14,680		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 23S: Proposed WS-1E



Summary for Pond DB-1: Det Basin

Inflow Area = 54,797 sf, 52.55% Impervious, Inflow Depth > 1.61" for 2-YR event
 Inflow = 2.51 cfs @ 12.09 hrs, Volume= 7,359 cf
 Outflow = 0.30 cfs @ 12.87 hrs, Volume= 3,456 cf, Atten= 88%, Lag= 46.6 min
 Primary = 0.30 cfs @ 12.87 hrs, Volume= 3,456 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 176.69' @ 12.87 hrs Surf.Area= 3,169 sf Storage= 4,261 cf
 Flood Elev= 178.00' Surf.Area= 4,254 sf Storage= 9,123 cf

Plug-Flow detention time= 192.6 min calculated for 3,445 cf (47% of inflow)
 Center-of-Mass det. time= 108.9 min (903.2 - 794.3)

Volume	Invert	Avail.Storage	Storage Description
#1	175.00'	9,123 cf	Basin A (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
175.00	1,904	0	0
176.00	2,630	2,267	2,267
177.00	3,414	3,022	5,289
178.00	4,254	3,834	9,123


Device	Routing	Invert	Outlet Devices
#1	Device 3	177.00'	2.0" x 2.0" Horiz. 12" x 24" grate X 10.00 columns X 5 rows C= 0.600 in 24.0" x 12.0" Grate (69% open area)
#2	Device 3	176.50'	6.0" Vert. Orifice/Grate X 3.00 C= 0.600 Limited to weir flow at low heads
#3	Primary	174.65'	12.0" Round HDPE Culvert L= 118.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 174.65' / 171.11' S= 0.0300 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=0.30 cfs @ 12.87 hrs HW=176.69' TW=0.00' (Dynamic Tailwater)

↑ 3=HDPE Culvert (Passes 0.30 cfs of 3.70 cfs potential flow)

- 1=12" x 24" grate (Controls 0.00 cfs)
- 2=Orifice/Grate (Orifice Controls 0.30 cfs @ 1.47 fps)

Pond DB-1: Det Basin



Summary for Pond IB-1: Infil Basin

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 0.83" for 2-YR event
 Inflow = 3.30 cfs @ 12.21 hrs, Volume= 8,872 cf
 Outflow = 0.09 cfs @ 20.00 hrs, Volume= 2,757 cf, Atten= 97%, Lag= 467.6 min
 Discarded = 0.09 cfs @ 20.00 hrs, Volume= 2,757 cf
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)
 Secondary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 172.18' @ 20.00 hrs Surf.Area= 3,997 sf Storage= 6,124 cf
 Flood Elev= 175.00' Surf.Area= 7,711 sf Storage= 22,476 cf

Plug-Flow detention time= 229.6 min calculated for 2,748 cf (31% of inflow)
 Center-of-Mass det. time= 126.3 min (951.5 - 825.2)

Volume	Invert	Avail.Storage	Storage Description
#1	170.00'	22,476 cf	Basin A (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
170.00	1,749	0	0
171.00	2,649	2,199	2,199
172.00	3,770	3,210	5,409
173.00	5,000	4,385	9,794
174.00	6,327	5,664	15,457
175.00	7,711	7,019	22,476

Device	Routing	Invert	Outlet Devices
#1	Discarded	170.00'	1.020 in/hr Exfiltration over Surface area
#2	Primary	170.00'	18.0" Round Culvert L= 45.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 170.00' / 169.10' S= 0.0200 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 1.77 sf
#3	Device 2	173.75'	2.0" x 2.0" Horiz. Orifice/Grate X 20.00 columns X 10 rows C= 0.600 in 48.0" x 24.0" Grate (69% open area)
#4	Device 2	173.00'	48.0" W x 9.0" H Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads
#5	Secondary	174.00'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Discarded OutFlow Max=0.09 cfs @ 20.00 hrs HW=172.18' (Free Discharge)

↑ 1=Exfiltration (Exfiltration Controls 0.09 cfs)

Primary OutFlow Max=0.00 cfs @ 5.00 hrs HW=170.00' TW=0.00' (Dynamic Tailwater)

↑ 2=Culvert (Controls 0.00 cfs)

↑ 3=Orifice/Grate (Controls 0.00 cfs)


↑ 4=Orifice/Grate (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 5.00 hrs HW=170.00' TW=0.00' (Dynamic Tailwater)

↑ 5=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond IB-1: Infil Basin

Hydrograph



Summary for Pond RG-1: Rain Garden

Inflow Area = 25,142 sf, 42.69% Impervious, Inflow Depth > 0.56" for 2-YR event
 Inflow = 0.33 cfs @ 12.11 hrs, Volume= 1,174 cf
 Outflow = 0.00 cfs @ 5.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)


Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 171.53' @ 20.00 hrs Surf.Area= 2,541 sf Storage= 1,173 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
 Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description	
#1	171.00'	4,257 cf	Custom Stage Data (Prismatic)	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	
171.00	1,856	0	0	
172.00	3,140	2,498	2,498	
172.50	3,897	1,759	4,257	

Device	Routing	Invert	Outlet Devices
#1	Primary	172.25'	30.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=0.00 cfs @ 5.00 hrs HW=171.00' TW=0.00' (Dynamic Tailwater)
 ↑ 1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond RG-1: Rain Garden

Summary for Pond UDS-1: Cultec 330 XLHD

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 1.40" for 2-YR event
 Inflow = 5.09 cfs @ 12.10 hrs, Volume= 14,951 cf
 Outflow = 3.30 cfs @ 12.21 hrs, Volume= 8,872 cf, Atten= 35%, Lag= 6.6 min
 Primary = 3.30 cfs @ 12.21 hrs, Volume= 8,872 cf
 Routed to Pond IB-1 : Infil Basin

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 172.18' @ 19.90 hrs Surf.Area= 0.142 ac Storage= 0.140 af
 Flood Elev= 174.00' Surf.Area= 0.142 ac Storage= 0.293 af

Plug-Flow detention time= 102.2 min calculated for 8,872 cf (59% of inflow)
 Center-of-Mass det. time= 23.3 min (825.2 - 801.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	171.00'	0.060 af	35.33'W x 115.50'L x 3.04'H Field A 0.285 af Overall - 0.136 af Embedded = 0.149 af x 40.0% Voids
#2A	171.00'	0.136 af	Cultec R-330XLHD x 112 Inside #1 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
#3B	171.00'	0.031 af	35.33'W x 59.50'L x 3.04'H Field B 0.147 af Overall - 0.069 af Embedded = 0.078 af x 40.0% Voids
#4B	171.00'	0.069 af	Cultec R-330XLHD x 56 Inside #3 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
		0.296 af	Total Available Storage

Storage Group A created with Chamber Wizard

Storage Group B created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	171.00'	15.0" Round Culvert X 4.00 L= 15.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 171.00' / 171.00' S= 0.0000 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=3.28 cfs @ 12.21 hrs HW=171.60' TW=171.06' (Dynamic Tailwater)
 ↑=Culvert (Barrel Controls 3.28 cfs @ 2.05 fps)

Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field A**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

16 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 113.50' Row Length +12.0" End Stone x 2 = 115.50' Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

112 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 5,919.8 cf Chamber Storage

12,413.0 cf Field - 5,919.8 cf Chambers = 6,493.2 cf Stone x 40.0% Voids = 2,597.3 cf Stone Storage

Chamber Storage + Stone Storage = 8,517.1 cf = 0.196 af


Overall Storage Efficiency = 68.6%

Overall System Size = 115.50' x 35.33' x 3.04'

112 Chambers

459.7 cy Field

240.5 cy Stone



Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field B**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

8 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 57.50' Row Length +12.0" End Stone x 2 = 59.50'

Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

56 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 2,999.0 cf Chamber Storage

6,394.6 cf Field - 2,999.0 cf Chambers = 3,395.6 cf Stone x 40.0% Voids = 1,358.2 cf Stone Storage

Chamber Storage + Stone Storage = 4,357.3 cf = 0.100 af


Overall Storage Efficiency = 68.1%

Overall System Size = 59.50' x 35.33' x 3.04'

56 Chambers

236.8 cy Field

125.8 cy Stone




23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Proposed Condition
Type III 24-hr 2-YR Rainfall=3.35"
Printed 12/6/2024
Page 22

Pond UDS-1: Cultec 330 XLHD




Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 309,868 sf, 37.48% Impervious, Inflow Depth > 0.33" for 2-YR event
Inflow = 1.27 cfs @ 12.10 hrs, Volume= 8,510 cf
Primary = 1.27 cfs @ 12.10 hrs, Volume= 8,510 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-1: Hunting Lane (Off-site)




Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 27,552 sf, 5.91% Impervious, Inflow Depth > 0.98" for 2-YR event
 Inflow = 0.75 cfs @ 12.10 hrs, Volume= 2,261 cf
 Primary = 0.75 cfs @ 12.10 hrs, Volume= 2,261 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-2: North Main Street (Offsite)




Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 20,492 sf, 0.00% Impervious, Inflow Depth > 0.17" for 2-YR event
 Inflow = 0.03 cfs @ 12.39 hrs, Volume= 297 cf
 Primary = 0.03 cfs @ 12.39 hrs, Volume= 297 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)



Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1S: Proposed WS-1A	Runoff Area=127,763 sf 45.93% Impervious Runoff Depth>2.90" Tc=6.0 min CN=80 Runoff=10.44 cfs 30,893 cf
Subcatchment7S: Proposed WS-1B	Runoff Area=25,142 sf 42.69% Impervious Runoff Depth>1.59" Tc=6.0 min CN=64 Runoff=1.10 cfs 3,325 cf
Subcatchment8S: Proposed WS-1C	Runoff Area=62,999 sf 5.13% Impervious Runoff Depth>0.97" Flow Length=970' Tc=37.8 min UI Adjusted CN=55 Runoff=0.79 cfs 5,080 cf
Subcatchment10S: Proposed WS-3	Runoff Area=27,552 sf 5.91% Impervious Runoff Depth>2.29" Tc=6.0 min UI Adjusted CN=73 Runoff=1.79 cfs 5,254 cf
Subcatchment11S: Proposed WS-4	Runoff Area=20,492 sf 0.00% Impervious Runoff Depth>0.81" Flow Length=195' Tc=6.4 min CN=52 Runoff=0.37 cfs 1,379 cf
Subcatchment17S: Proposed WS-1D	Runoff Area=54,797 sf 52.55% Impervious Runoff Depth>3.18" Tc=6.0 min CN=83 Runoff=4.87 cfs 14,536 cf
Subcatchment23S: Proposed WS-1E	Runoff Area=39,167 sf 37.48% Impervious Runoff Depth>2.54" Tc=6.0 min CN=76 Runoff=2.83 cfs 8,303 cf
Pond DB-1: Det Basin	Peak Elev=177.08' Storage=5,549 cf Inflow=4.87 cfs 14,536 cf Outflow=3.46 cfs 10,562 cf
Pond IB-1: Infil Basin Discarded=0.12 cfs 3,911 cf Primary=0.58 cfs 7,030 cf Secondary=0.00 cfs 0 cf	Peak Elev=173.13' Storage=10,440 cf Inflow=5.75 cfs 20,895 cf Outflow=0.70 cfs 10,942 cf
Pond RG-1: Rain Garden	Peak Elev=172.25' Storage=3,323 cf Inflow=1.10 cfs 3,325 cf Outflow=0.00 cfs 0 cf
Pond UDS-1: Cultec 330 XLHD 15.0" Round Culvert x 4.00 n=0.012 L=15.0' S=0.0000 '/'	Peak Elev=173.13' Storage=0.238 af Inflow=10.44 cfs 30,893 cf Outflow=5.75 cfs 20,895 cf
Link POA-1: Hunting Lane (Off-site)	Inflow=5.92 cfs 30,975 cf Primary=5.92 cfs 30,975 cf
Link POA-2: North Main Street (Offsite)	Inflow=1.79 cfs 5,254 cf Primary=1.79 cfs 5,254 cf
Link POA-3: 33 N Main Street (Offsite)	Inflow=0.37 cfs 1,379 cf Primary=0.37 cfs 1,379 cf

Total Runoff Area = 357,912 sf Runoff Volume = 68,770 cf Average Runoff Depth = 2.31"
67.10% Pervious = 240,161 sf 32.90% Impervious = 117,751 sf

Summary for Subcatchment 1S: Proposed WS-1A

Runoff = 10.44 cfs @ 12.09 hrs, Volume= 30,893 cf, Depth> 2.90"
 Routed to Pond UDS-1 : Cultec 330 XLHD


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description
2,745	98	Unconnected pavement, HSG A
33,953	98	Unconnected pavement, HSG B
21,986	98	Unconnected pavement, HSG C
1,946	39	>75% Grass cover, Good, HSG A
41,046	61	>75% Grass cover, Good, HSG B
26,087	74	>75% Grass cover, Good, HSG C
127,763	80	Weighted Average
69,079		54.07% Pervious Area
58,684		45.93% Impervious Area
58,684		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 1S: Proposed WS-1A

Hydrograph




Summary for Subcatchment 7S: Proposed WS-1B

Runoff = 1.10 cfs @ 12.10 hrs, Volume= 3,325 cf, Depth> 1.59"
Routed to Pond RG-1 : Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description
10,733	98	Unconnected pavement, HSG A
0	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
14,409	39	>75% Grass cover, Good, HSG A
0	61	>75% Grass cover, Good, HSG B
0	74	>75% Grass cover, Good, HSG C
25,142	64	Weighted Average
14,409		57.31% Pervious Area
10,733		42.69% Impervious Area
10,733		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 7S: Proposed WS-1B

23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Proposed Condition

Type III 24-hr 10-YR Rainfall=5.24"

Printed 12/6/2024

Page 29

Summary for Subcatchment 8S: Proposed WS-1C


Runoff = 0.79 cfs @ 12.62 hrs, Volume= 5,080 cf, Depth> 0.97"
Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Adj	Description
0	98		Unconnected pavement, HSG A
3,231	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
18,478	39		>75% Grass cover, Good, HSG A
41,290	61		>75% Grass cover, Good, HSG B
0	74		>75% Grass cover, Good, HSG C

62,999	56	55	Weighted Average, UI Adjusted
59,768			94.87% Pervious Area
3,231			5.13% Impervious Area
3,231			100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.6	50	0.0100	0.08		Sheet Flow, Grass: Dense n= 0.240 P2= 3.35"
27.2	920	0.0065	0.56		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
37.8	970	Total			

Subcatchment 8S: Proposed WS-1C


Summary for Subcatchment 10S: Proposed WS-3

Runoff = 1.79 cfs @ 12.09 hrs, Volume= 5,254 cf, Depth> 2.29"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Adj	Description
38	98		Unconnected pavement, HSG A
1,589	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
1,223	39		>75% Grass cover, Good, HSG A
0	61		>75% Grass cover, Good, HSG B
24,702	74		>75% Grass cover, Good, HSG C
27,552	74	73	Weighted Average, UI Adjusted
25,925			94.09% Pervious Area
1,627			5.91% Impervious Area
1,627			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
Capacity (cfs)			Description
6.0			Direct Entry,

Subcatchment 10S: Proposed WS-3




Summary for Subcatchment 11S: Proposed WS-4

Runoff = 0.37 cfs @ 12.12 hrs, Volume= 1,379 cf, Depth> 0.81"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description		
0	98	Unconnected pavement, HSG A		
0	98	Unconnected pavement, HSG B		
0	98	Unconnected pavement, HSG C		
8,496	39	>75% Grass cover, Good, HSG A		
11,996	61	>75% Grass cover, Good, HSG B		
0	74	>75% Grass cover, Good, HSG C		
20,492	52	Weighted Average		
20,492		100.00% Pervious Area		
Tc	Length (feet)	Slope (ft/ft)		
4.9	50	0.0700		
1.5	145	0.0520		
6.4	195	Total		
(min)	(ft/sec)	Velocity (ft/sec)	Capacity (cfs)	Description
				Sheet Flow, Grass: Dense n= 0.240 P2= 3.35"
				Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps

Subcatchment 11S: Proposed WS-4



23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Proposed Condition
Type III 24-hr 10-YR Rainfall=5.24"
Printed 12/6/2024
Page 33

Summary for Subcatchment 17S: Proposed WS-1D


Runoff = 4.87 cfs @ 12.09 hrs, Volume= 14,536 cf, Depth> 3.18"
Routed to Pond DB-1 : Det Basin

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
17,482	98	Unconnected pavement, HSG B
11,314	98	Unconnected pavement, HSG C
0	39	>75% Grass cover, Good, HSG A
13,949	61	>75% Grass cover, Good, HSG B
12,052	74	>75% Grass cover, Good, HSG C
54,797	83	Weighted Average
26,001		47.45% Pervious Area
28,796		52.55% Impervious Area
28,796		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 17S: Proposed WS-1D



Summary for Subcatchment 23S: Proposed WS-1E


Runoff = 2.83 cfs @ 12.09 hrs, Volume= 8,303 cf, Depth> 2.54"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 10-YR Rainfall=5.24"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
14,680	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
0	39	>75% Grass cover, Good, HSG A
21,286	61	>75% Grass cover, Good, HSG B
3,201	74	>75% Grass cover, Good, HSG C
39,167	76	Weighted Average
24,487		62.52% Pervious Area
14,680		37.48% Impervious Area
14,680		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 23S: Proposed WS-1E



Summary for Pond DB-1: Det Basin

Inflow Area = 54,797 sf, 52.55% Impervious, Inflow Depth > 3.18" for 10-YR event
 Inflow = 4.87 cfs @ 12.09 hrs, Volume= 14,536 cf
 Outflow = 3.46 cfs @ 12.18 hrs, Volume= 10,562 cf, Atten= 29%, Lag= 5.1 min
 Primary = 3.46 cfs @ 12.18 hrs, Volume= 10,562 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 177.08' @ 12.18 hrs Surf.Area= 3,477 sf Storage= 5,549 cf
 Flood Elev= 178.00' Surf.Area= 4,254 sf Storage= 9,123 cf

Plug-Flow detention time= 115.4 min calculated for 10,527 cf (72% of inflow)
 Center-of-Mass det. time= 53.4 min (831.9 - 778.5)


Volume	Invert	Avail.Storage	Storage Description
#1	175.00'	9,123 cf	Basin A (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
175.00	1,904	0	0
176.00	2,630	2,267	2,267
177.00	3,414	3,022	5,289
178.00	4,254	3,834	9,123

Device	Routing	Invert	Outlet Devices
#1	Device 3	177.00'	2.0" x 2.0" Horiz. 12" x 24" grate X 10.00 columns X 5 rows C= 0.600 in 24.0" x 12.0" Grate (69% open area)
#2	Device 3	176.50'	6.0" Vert. Orifice/Grate X 3.00 C= 0.600 Limited to weir flow at low heads
#3	Primary	174.65'	12.0" Round HDPE Culvert L= 118.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 174.65' / 171.11' S= 0.0300 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=3.41 cfs @ 12.18 hrs HW=177.07' TW=0.00' (Dynamic Tailwater)

↑ 3=HDPE Culvert (Passes 3.41 cfs of 4.14 cfs potential flow)
 └─1=12" x 24" grate (Orifice Controls 1.80 cfs @ 1.29 fps)
 └─2=Orifice/Grate (Orifice Controls 1.61 cfs @ 2.73 fps)

Pond DB-1: Det Basin



Summary for Pond IB-1: Infil Basin

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 1.96" for 10-YR event
 Inflow = 5.75 cfs @ 12.09 hrs, Volume= 20,895 cf
 Outflow = 0.70 cfs @ 13.86 hrs, Volume= 10,942 cf, Atten= 88%, Lag= 105.9 min
 Discarded = 0.12 cfs @ 13.86 hrs, Volume= 3,911 cf
 Primary = 0.58 cfs @ 13.86 hrs, Volume= 7,030 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)
 Secondary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 173.13' @ 13.86 hrs Surf.Area= 5,169 sf Storage= 10,440 cf
 Flood Elev= 175.00' Surf.Area= 7,711 sf Storage= 22,476 cf

Plug-Flow detention time= 206.0 min calculated for 10,905 cf (52% of inflow)
 Center-of-Mass det. time= 102.1 min (925.0 - 823.0)

Volume	Invert	Avail.Storage	Storage Description
#1	170.00'	22,476 cf	Basin A (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
170.00	1,749	0	0
171.00	2,649	2,199	2,199
172.00	3,770	3,210	5,409
173.00	5,000	4,385	9,794
174.00	6,327	5,664	15,457
175.00	7,711	7,019	22,476

Device	Routing	Invert	Outlet Devices
#1	Discarded	170.00'	1.020 in/hr Exfiltration over Surface area
#2	Primary	170.00'	18.0" Round Culvert L= 45.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 170.00' / 169.10' S= 0.0200 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 1.77 sf
#3	Device 2	173.75'	2.0" x 2.0" Horiz. Orifice/Grate X 20.00 columns X 10 rows C= 0.600 in 48.0" x 24.0" Grate (69% open area)
#4	Device 2	173.00'	48.0" W x 9.0" H Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads
#5	Secondary	174.00'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Discarded OutFlow Max=0.12 cfs @ 13.86 hrs HW=173.13' (Free Discharge)

↑ 1=Exfiltration (Exfiltration Controls 0.12 cfs)

Primary OutFlow Max=0.58 cfs @ 13.86 hrs HW=173.13' TW=0.00' (Dynamic Tailwater)

↑ 2=Culvert (Passes 0.58 cfs of 10.36 cfs potential flow)

↑ 3=Orifice/Grate (Controls 0.00 cfs)


↑ 4=Orifice/Grate (Orifice Controls 0.58 cfs @ 1.14 fps)

Secondary OutFlow Max=0.00 cfs @ 5.00 hrs HW=170.00' TW=0.00' (Dynamic Tailwater)

↑ 5=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond IB-1: Infil Basin

Hydrograph



Summary for Pond RG-1: Rain Garden

Inflow Area = 25,142 sf, 42.69% Impervious, Inflow Depth > 1.59" for 10-YR event
 Inflow = 1.10 cfs @ 12.10 hrs, Volume= 3,325 cf
 Outflow = 0.00 cfs @ 5.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)


Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 172.25' @ 20.00 hrs Surf.Area= 3,515 sf Storage= 3,323 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
 Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description	
#1	171.00'	4,257 cf	Custom Stage Data (Prismatic)	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	
171.00	1,856	0	0	
172.00	3,140	2,498	2,498	
172.50	3,897	1,759	4,257	
Device	Routing	Invert	Outlet Devices	
#1	Primary	172.25'	30.0' long x 3.0' breadth Broad-Crested Rectangular Weir	
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00	
			2.50 3.00 3.50 4.00 4.50	
			Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68	
			2.72 2.81 2.92 2.97 3.07 3.32	

Primary OutFlow Max=0.00 cfs @ 5.00 hrs HW=171.00' TW=0.00' (Dynamic Tailwater)
 ↑ 1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond RG-1: Rain Garden



Summary for Pond UDS-1: Cultec 330 XLHD

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 2.90" for 10-YR event
 Inflow = 10.44 cfs @ 12.09 hrs, Volume= 30,893 cf
 Outflow = 5.75 cfs @ 12.09 hrs, Volume= 20,895 cf, Atten= 45%, Lag= 0.0 min
 Primary = 5.75 cfs @ 12.09 hrs, Volume= 20,895 cf
 Routed to Pond IB-1 : Infil Basin

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 173.13' @ 13.90 hrs Surf.Area= 0.142 ac Storage= 0.238 af
 Flood Elev= 174.00' Surf.Area= 0.142 ac Storage= 0.293 af

Plug-Flow detention time= 105.8 min calculated for 20,826 cf (67% of inflow)
 Center-of-Mass det. time= 37.6 min (823.0 - 785.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	171.00'	0.060 af	35.33'W x 115.50'L x 3.04'H Field A 0.285 af Overall - 0.136 af Embedded = 0.149 af x 40.0% Voids
#2A	171.00'	0.136 af	Cultec R-330XLHD x 112 Inside #1 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
#3B	171.00'	0.031 af	35.33'W x 59.50'L x 3.04'H Field B 0.147 af Overall - 0.069 af Embedded = 0.078 af x 40.0% Voids
#4B	171.00'	0.069 af	Cultec R-330XLHD x 56 Inside #3 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
		0.296 af	Total Available Storage

Storage Group A created with Chamber Wizard

Storage Group B created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	171.00'	15.0" Round Culvert X 4.00 L= 15.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 171.00' / 171.00' S= 0.0000 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=0.00 cfs @ 12.09 hrs HW=171.88' TW=171.97' (Dynamic Tailwater)
 ↑=Culvert (Controls 0.00 cfs)

Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field A**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

16 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 113.50' Row Length +12.0" End Stone x 2 = 115.50' Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

112 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 5,919.8 cf Chamber Storage

12,413.0 cf Field - 5,919.8 cf Chambers = 6,493.2 cf Stone x 40.0% Voids = 2,597.3 cf Stone Storage

Chamber Storage + Stone Storage = 8,517.1 cf = 0.196 af


Overall Storage Efficiency = 68.6%

Overall System Size = 115.50' x 35.33' x 3.04'

112 Chambers

459.7 cy Field

240.5 cy Stone



Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field B**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

8 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 57.50' Row Length +12.0" End Stone x 2 = 59.50'

Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

56 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 2,999.0 cf Chamber Storage

6,394.6 cf Field - 2,999.0 cf Chambers = 3,395.6 cf Stone x 40.0% Voids = 1,358.2 cf Stone Storage

Chamber Storage + Stone Storage = 4,357.3 cf = 0.100 af


Overall Storage Efficiency = 68.1%

Overall System Size = 59.50' x 35.33' x 3.04'


56 Chambers

236.8 cy Field

125.8 cy Stone



Pond UDS-1: Cultec 330 XLHD




Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 309,868 sf, 37.48% Impervious, Inflow Depth > 1.20" for 10-YR event

Inflow = 5.92 cfs @ 12.16 hrs, Volume= 30,975 cf

Primary = 5.92 cfs @ 12.16 hrs, Volume= 30,975 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs


Link POA-1: Hunting Lane (Off-site)

Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 27,552 sf, 5.91% Impervious, Inflow Depth > 2.29" for 10-YR event
 Inflow = 1.79 cfs @ 12.09 hrs, Volume= 5,254 cf
 Primary = 1.79 cfs @ 12.09 hrs, Volume= 5,254 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs


Link POA-2: North Main Street (Offsite)



Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 20,492 sf, 0.00% Impervious, Inflow Depth > 0.81" for 10-YR event
Inflow = 0.37 cfs @ 12.12 hrs, Volume= 1,379 cf
Primary = 0.37 cfs @ 12.12 hrs, Volume= 1,379 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1S: Proposed WS-1A	Runoff Area=127,763 sf 45.93% Impervious Runoff Depth>3.91" Tc=6.0 min CN=80 Runoff=13.92 cfs 41,589 cf
Subcatchment7S: Proposed WS-1B	Runoff Area=25,142 sf 42.69% Impervious Runoff Depth>2.36" Tc=6.0 min CN=64 Runoff=1.67 cfs 4,950 cf
Subcatchment8S: Proposed WS-1C	Runoff Area=62,999 sf 5.13% Impervious Runoff Depth>1.57" Flow Length=970' Tc=37.8 min UI Adjusted CN=55 Runoff=1.38 cfs 8,258 cf
Subcatchment10S: Proposed WS-3	Runoff Area=27,552 sf 5.91% Impervious Runoff Depth>3.20" Tc=6.0 min UI Adjusted CN=73 Runoff=2.50 cfs 7,356 cf
Subcatchment11S: Proposed WS-4	Runoff Area=20,492 sf 0.00% Impervious Runoff Depth>1.36" Flow Length=195' Tc=6.4 min CN=52 Runoff=0.71 cfs 2,326 cf
Subcatchment17S: Proposed WS-1D	Runoff Area=54,797 sf 52.55% Impervious Runoff Depth>4.22" Tc=6.0 min CN=83 Runoff=6.37 cfs 19,270 cf
Subcatchment23S: Proposed WS-1E	Runoff Area=39,167 sf 37.48% Impervious Runoff Depth>3.50" Tc=6.0 min CN=76 Runoff=3.87 cfs 11,423 cf
Pond DB-1: Det Basin	Peak Elev=177.28' Storage=6,276 cf Inflow=6.37 cfs 19,270 cf Outflow=4.36 cfs 15,259 cf
Pond IB-1: Infil Basin Discarded=0.13 cfs 4,181 cf Primary=2.72 cfs 17,340 cf Secondary=0.00 cfs 0 cf	Peak Elev=173.36' Storage=11,654 cf Inflow=6.95 cfs 31,540 cf Outflow=2.85 cfs 21,521 cf
Pond RG-1: Rain Garden	Peak Elev=172.27' Storage=3,383 cf Inflow=1.67 cfs 4,950 cf Outflow=0.13 cfs 1,598 cf
Pond UDS-1: Cultec 330 XLHD 15.0" Round Culvert x 4.00 n=0.012 L=15.0' S=0.0000 '/'	Peak Elev=173.37' Storage=0.257 af Inflow=13.92 cfs 41,589 cf Outflow=6.95 cfs 31,540 cf
Link POA-1: Hunting Lane (Off-site)	Inflow=8.41 cfs 53,877 cf Primary=8.41 cfs 53,877 cf
Link POA-2: North Main Street (Offsite)	Inflow=2.50 cfs 7,356 cf Primary=2.50 cfs 7,356 cf
Link POA-3: 33 N Main Street (Offsite)	Inflow=0.71 cfs 2,326 cf Primary=0.71 cfs 2,326 cf

Total Runoff Area = 357,912 sf Runoff Volume = 95,171 cf Average Runoff Depth = 3.19"
67.10% Pervious = 240,161 sf 32.90% Impervious = 117,751 sf

Summary for Subcatchment 1S: Proposed WS-1A


Runoff = 13.92 cfs @ 12.09 hrs, Volume= 41,589 cf, Depth> 3.91"
 Routed to Pond UDS-1 : Cultec 330 XLHD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description
2,745	98	Unconnected pavement, HSG A
33,953	98	Unconnected pavement, HSG B
21,986	98	Unconnected pavement, HSG C
1,946	39	>75% Grass cover, Good, HSG A
41,046	61	>75% Grass cover, Good, HSG B
26,087	74	>75% Grass cover, Good, HSG C
127,763	80	Weighted Average
69,079		54.07% Pervious Area
58,684		45.93% Impervious Area
58,684		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 1S: Proposed WS-1A




Summary for Subcatchment 7S: Proposed WS-1B

Runoff = 1.67 cfs @ 12.10 hrs, Volume= 4,950 cf, Depth> 2.36"
Routed to Pond RG-1 : Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description
10,733	98	Unconnected pavement, HSG A
0	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
14,409	39	>75% Grass cover, Good, HSG A
0	61	>75% Grass cover, Good, HSG B
0	74	>75% Grass cover, Good, HSG C
25,142	64	Weighted Average
14,409		57.31% Pervious Area
10,733		42.69% Impervious Area
10,733		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 7S: Proposed WS-1B


Summary for Subcatchment 8S: Proposed WS-1C

Runoff = 1.38 cfs @ 12.58 hrs, Volume= 8,258 cf, Depth> 1.57"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Adj	Description
0	98		Unconnected pavement, HSG A
3,231	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
18,478	39		>75% Grass cover, Good, HSG A
41,290	61		>75% Grass cover, Good, HSG B
0	74		>75% Grass cover, Good, HSG C
62,999	56	55	Weighted Average, UI Adjusted
59,768			94.87% Pervious Area
3,231			5.13% Impervious Area
3,231			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
10.6	50	0.0100	0.08
27.2	920	0.0065	0.56
37.8	970	Total	
			Sheet Flow, Grass: Dense n= 0.240 P2= 3.35" Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps

Subcatchment 8S: Proposed WS-1C




Summary for Subcatchment 10S: Proposed WS-3

Runoff = 2.50 cfs @ 12.09 hrs, Volume= 7,356 cf, Depth> 3.20"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Adj	Description
38	98		Unconnected pavement, HSG A
1,589	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
1,223	39		>75% Grass cover, Good, HSG A
0	61		>75% Grass cover, Good, HSG B
24,702	74		>75% Grass cover, Good, HSG C
27,552	74	73	Weighted Average, UI Adjusted
25,925			94.09% Pervious Area
1,627			5.91% Impervious Area
1,627			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
Capacity (cfs)			Description
6.0			Direct Entry,

Subcatchment 10S: Proposed WS-3



Summary for Subcatchment 11S: Proposed WS-4


Runoff = 0.71 cfs @ 12.11 hrs, Volume= 2,326 cf, Depth> 1.36"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description		
0	98	Unconnected pavement, HSG A		
0	98	Unconnected pavement, HSG B		
0	98	Unconnected pavement, HSG C		
8,496	39	>75% Grass cover, Good, HSG A		
11,996	61	>75% Grass cover, Good, HSG B		
0	74	>75% Grass cover, Good, HSG C		
20,492	52	Weighted Average		
20,492		100.00% Pervious Area		
Tc	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
4.9	50	0.0700	0.17	Sheet Flow, Grass: Dense n= 0.240 P2= 3.35"
1.5	145	0.0520	1.60	Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
6.4	195	Total		

Subcatchment 11S: Proposed WS-4

Hydrograph




Summary for Subcatchment 17S: Proposed WS-1D

Runoff = 6.37 cfs @ 12.09 hrs, Volume= 19,270 cf, Depth> 4.22"
 Routed to Pond DB-1 : Det Basin

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description	
0	98	Unconnected pavement, HSG A	
17,482	98	Unconnected pavement, HSG B	
11,314	98	Unconnected pavement, HSG C	
0	39	>75% Grass cover, Good, HSG A	
13,949	61	>75% Grass cover, Good, HSG B	
12,052	74	>75% Grass cover, Good, HSG C	
54,797	83	Weighted Average	
26,001		47.45% Pervious Area	
28,796		52.55% Impervious Area	
28,796		100.00% Unconnected	
Tc	Length (feet)	Slope (ft/ft)	
(min)		Velocity (ft/sec)	
		Capacity (cfs)	
6.0			Direct Entry,

Subcatchment 17S: Proposed WS-1D



23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Proposed Condition
Type III 24-hr 25-YR Rainfall=6.42"
Printed 12/6/2024
Page 56

Summary for Subcatchment 23S: Proposed WS-1E


Runoff = 3.87 cfs @ 12.09 hrs, Volume= 11,423 cf, Depth> 3.50"
Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 25-YR Rainfall=6.42"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
14,680	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
0	39	>75% Grass cover, Good, HSG A
21,286	61	>75% Grass cover, Good, HSG B
3,201	74	>75% Grass cover, Good, HSG C
39,167	76	Weighted Average
24,487		62.52% Pervious Area
14,680		37.48% Impervious Area
14,680		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 23S: Proposed WS-1E



Summary for Pond DB-1: Det Basin

Inflow Area = 54,797 sf, 52.55% Impervious, Inflow Depth > 4.22" for 25-YR event
 Inflow = 6.37 cfs @ 12.09 hrs, Volume= 19,270 cf
 Outflow = 4.36 cfs @ 12.18 hrs, Volume= 15,259 cf, Atten= 32%, Lag= 5.3 min
 Primary = 4.36 cfs @ 12.18 hrs, Volume= 15,259 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 177.28' @ 12.18 hrs Surf.Area= 3,649 sf Storage= 6,276 cf
 Flood Elev= 178.00' Surf.Area= 4,254 sf Storage= 9,123 cf

Plug-Flow detention time= 98.7 min calculated for 15,208 cf (79% of inflow)
 Center-of-Mass det. time= 45.7 min (817.5 - 771.8)


Volume	Invert	Avail.Storage	Storage Description
#1	175.00'	9,123 cf	Basin A (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
175.00	1,904	0	0
176.00	2,630	2,267	2,267
177.00	3,414	3,022	5,289
178.00	4,254	3,834	9,123

Device	Routing	Invert	Outlet Devices
#1	Device 3	177.00'	2.0" x 2.0" Horiz. 12" x 24" grate X 10.00 columns X 5 rows C= 0.600 in 24.0" x 12.0" Grate (69% open area)
#2	Device 3	176.50'	6.0" Vert. Orifice/Grate X 3.00 C= 0.600 Limited to weir flow at low heads
#3	Primary	174.65'	12.0" Round HDPE Culvert L= 118.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 174.65' / 171.11' S= 0.0300 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=4.35 cfs @ 12.18 hrs HW=177.27' TW=0.00' (Dynamic Tailwater)

↑ 3=HDPE Culvert (Inlet Controls 4.35 cfs @ 5.54 fps)
 └─1=12" x 24" grate (Passes < 3.50 cfs potential flow)
 └─2=Orifice/Grate (Passes < 2.05 cfs potential flow)

Pond DB-1: Det Basin



Summary for Pond IB-1: Infil Basin

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 2.96" for 25-YR event
 Inflow = 6.95 cfs @ 12.10 hrs, Volume= 31,540 cf
 Outflow = 2.85 cfs @ 12.52 hrs, Volume= 21,521 cf, Atten= 59%, Lag= 25.2 min
 Discarded = 0.13 cfs @ 12.52 hrs, Volume= 4,181 cf
 Primary = 2.72 cfs @ 12.52 hrs, Volume= 17,340 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)
 Secondary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 173.36' @ 12.52 hrs Surf.Area= 5,472 sf Storage= 11,654 cf
 Flood Elev= 175.00' Surf.Area= 7,711 sf Storage= 22,476 cf

Plug-Flow detention time= 135.7 min calculated for 21,521 cf (68% of inflow)
 Center-of-Mass det. time= 59.7 min (868.4 - 808.7)

Volume	Invert	Avail.Storage	Storage Description
#1	170.00'	22,476 cf	Basin A (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
170.00	1,749	0	0
171.00	2,649	2,199	2,199
172.00	3,770	3,210	5,409
173.00	5,000	4,385	9,794
174.00	6,327	5,664	15,457
175.00	7,711	7,019	22,476
Device	Routing	Invert	Outlet Devices
#1	Discarded	170.00'	1.020 in/hr Exfiltration over Surface area
#2	Primary	170.00'	18.0" Round Culvert L= 45.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 170.00' / 169.10' S= 0.0200 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 1.77 sf
#3	Device 2	173.75'	2.0" x 2.0" Horiz. Orifice/Grate X 20.00 columns X 10 rows C= 0.600 in 48.0" x 24.0" Grate (69% open area)
#4	Device 2	173.00'	48.0" W x 9.0" H Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads
#5	Secondary	174.00'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32


Discarded OutFlow Max=0.13 cfs @ 12.52 hrs HW=173.35' (Free Discharge)
 ↑ 1=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=2.70 cfs @ 12.52 hrs HW=173.35' TW=0.00' (Dynamic Tailwater)
 ↑ 2=Culvert (Passes 2.70 cfs of 10.84 cfs potential flow)
 ↑ 3=Orifice/Grate (Controls 0.00 cfs)
 ↑ 4=Orifice/Grate (Orifice Controls 2.70 cfs @ 1.91 fps)

Secondary OutFlow Max=0.00 cfs @ 5.00 hrs HW=170.00' TW=0.00' (Dynamic Tailwater)
 ↑ 5=Broad-Crested Rectangular Weir(Controls 0.00 cfs)

Pond IB-1: Infil Basin

Hydrograph



Summary for Pond RG-1: Rain Garden

Inflow Area = 25,142 sf, 42.69% Impervious, Inflow Depth > 2.36" for 25-YR event
 Inflow = 1.67 cfs @ 12.10 hrs, Volume= 4,950 cf
 Outflow = 0.13 cfs @ 13.86 hrs, Volume= 1,598 cf, Atten= 92%, Lag= 106.0 min
 Primary = 0.13 cfs @ 13.86 hrs, Volume= 1,598 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 172.27' @ 13.86 hrs Surf.Area= 3,541 sf Storage= 3,383 cf


Plug-Flow detention time= 248.9 min calculated for 1,592 cf (32% of inflow)
 Center-of-Mass det. time= 154.7 min (963.1 - 808.4)

Volume	Invert	Avail.Storage	Storage Description	
#1	171.00'	4,257 cf	Custom Stage Data (Prismatic)	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	
171.00	1,856	0	0	
172.00	3,140	2,498	2,498	
172.50	3,897	1,759	4,257	

Device	Routing	Invert	Outlet Devices	
#1	Primary	172.25'	30.0' long x 3.0' breadth Broad-Crested Rectangular Weir	
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00	
			2.50 3.00 3.50 4.00 4.50	
			Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68	
			2.72 2.81 2.92 2.97 3.07 3.32	

Primary OutFlow Max=0.13 cfs @ 13.86 hrs HW=172.26' TW=0.00' (Dynamic Tailwater)
 ↑ 1=Broad-Crested Rectangular Weir (Weir Controls 0.13 cfs @ 0.30 fps)

Pond RG-1: Rain Garden



Summary for Pond UDS-1: Cultec 330 XLHD

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 3.91" for 25-YR event
 Inflow = 13.92 cfs @ 12.09 hrs, Volume= 41,589 cf
 Outflow = 6.95 cfs @ 12.10 hrs, Volume= 31,540 cf, Atten= 50%, Lag= 0.5 min
 Primary = 6.95 cfs @ 12.10 hrs, Volume= 31,540 cf
 Routed to Pond IB-1 : Infil Basin

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 173.37' @ 12.55 hrs Surf.Area= 0.142 ac Storage= 0.257 af
 Flood Elev= 174.00' Surf.Area= 0.142 ac Storage= 0.293 af

Plug-Flow detention time= 88.6 min calculated for 31,435 cf (76% of inflow)
 Center-of-Mass det. time= 30.3 min (808.7 - 778.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	171.00'	0.060 af	35.33'W x 115.50'L x 3.04'H Field A 0.285 af Overall - 0.136 af Embedded = 0.149 af x 40.0% Voids
#2A	171.00'	0.136 af	Cultec R-330XLHD x 112 Inside #1 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
#3B	171.00'	0.031 af	35.33'W x 59.50'L x 3.04'H Field B 0.147 af Overall - 0.069 af Embedded = 0.078 af x 40.0% Voids
#4B	171.00'	0.069 af	Cultec R-330XLHD x 56 Inside #3 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
		0.296 af	Total Available Storage

Storage Group A created with Chamber Wizard

Storage Group B created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	171.00'	15.0" Round Culvert X 4.00 L= 15.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 171.00' / 171.00' S= 0.0000 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=0.00 cfs @ 12.10 hrs HW=172.40' TW=172.53' (Dynamic Tailwater)
 ↑=Culvert (Controls 0.00 cfs)

Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field A**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

16 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 113.50' Row Length +12.0" End Stone x 2 = 115.50' Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

112 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 5,919.8 cf Chamber Storage

12,413.0 cf Field - 5,919.8 cf Chambers = 6,493.2 cf Stone x 40.0% Voids = 2,597.3 cf Stone Storage

Chamber Storage + Stone Storage = 8,517.1 cf = 0.196 af


Overall Storage Efficiency = 68.6%

Overall System Size = 115.50' x 35.33' x 3.04'

112 Chambers

459.7 cy Field

240.5 cy Stone



Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field B**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

8 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 57.50' Row Length +12.0" End Stone x 2 = 59.50'

Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

56 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 2,999.0 cf Chamber Storage

6,394.6 cf Field - 2,999.0 cf Chambers = 3,395.6 cf Stone x 40.0% Voids = 1,358.2 cf Stone Storage

Chamber Storage + Stone Storage = 4,357.3 cf = 0.100 af


Overall Storage Efficiency = 68.1%

Overall System Size = 59.50' x 35.33' x 3.04'


56 Chambers

236.8 cy Field

125.8 cy Stone



Pond UDS-1: Cultec 330 XLHD




Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 309,868 sf, 37.48% Impervious, Inflow Depth > 2.09" for 25-YR event

Inflow = 8.41 cfs @ 12.11 hrs, Volume= 53,877 cf

Primary = 8.41 cfs @ 12.11 hrs, Volume= 53,877 cf, Atten= 0%, Lag= 0.0 min


Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-1: Hunting Lane (Off-site)

Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 27,552 sf, 5.91% Impervious, Inflow Depth > 3.20" for 25-YR event
Inflow = 2.50 cfs @ 12.09 hrs, Volume= 7,356 cf
Primary = 2.50 cfs @ 12.09 hrs, Volume= 7,356 cf, Atten= 0%, Lag= 0.0 min


Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-2: North Main Street (Offsite)

Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 20,492 sf, 0.00% Impervious, Inflow Depth > 1.36" for 25-YR event
Inflow = 0.71 cfs @ 12.11 hrs, Volume= 2,326 cf
Primary = 0.71 cfs @ 12.11 hrs, Volume= 2,326 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment1S: Proposed WS-1A	Runoff Area=127,763 sf 45.93% Impervious Runoff Depth>5.50" Tc=6.0 min CN=80 Runoff=19.31 cfs 58,581 cf
Subcatchment7S: Proposed WS-1B	Runoff Area=25,142 sf 42.69% Impervious Runoff Depth>3.68" Tc=6.0 min CN=64 Runoff=2.62 cfs 7,704 cf
Subcatchment8S: Proposed WS-1C	Runoff Area=62,999 sf 5.13% Impervious Runoff Depth>2.66" Flow Length=970' Tc=37.8 min UI Adjusted CN=55 Runoff=2.43 cfs 13,952 cf
Subcatchment10S: Proposed WS-3	Runoff Area=27,552 sf 5.91% Impervious Runoff Depth>4.69" Tc=6.0 min UI Adjusted CN=73 Runoff=3.63 cfs 10,777 cf
Subcatchment11S: Proposed WS-4	Runoff Area=20,492 sf 0.00% Impervious Runoff Depth>2.38" Flow Length=195' Tc=6.4 min CN=52 Runoff=1.32 cfs 4,060 cf
Subcatchment17S: Proposed WS-1D	Runoff Area=54,797 sf 52.55% Impervious Runoff Depth>5.85" Tc=6.0 min CN=83 Runoff=8.68 cfs 26,720 cf
Subcatchment23S: Proposed WS-1E	Runoff Area=39,167 sf 37.48% Impervious Runoff Depth>5.04" Tc=6.0 min CN=76 Runoff=5.50 cfs 16,446 cf
Pond DB-1: Det Basin	Peak Elev=177.65' Storage=7,680 cf Inflow=8.68 cfs 26,720 cf Outflow=4.72 cfs 22,659 cf
Pond IB-1: Infil Basin Discarded=0.14 cfs 4,532 cf Primary=8.26 cfs 33,828 cf Secondary=0.00 cfs 0 cf	Peak Elev=173.75' Storage=13,887 cf Inflow=12.26 cfs 48,465 cf Outflow=8.40 cfs 38,361 cf
Pond RG-1: Rain Garden	Peak Elev=172.31' Storage=3,544 cf Inflow=2.62 cfs 7,704 cf Outflow=1.07 cfs 4,346 cf
Pond UDS-1: Cultec 330 XLHD 15.0" Round Culvert x 4.00 n=0.012 L=15.0' S=0.0000 '/'	Peak Elev=173.93' Storage=0.289 af Inflow=19.31 cfs 58,581 cf Outflow=12.26 cfs 48,465 cf
Link POA-1: Hunting Lane (Off-site)	Inflow=17.73 cfs 91,231 cf Primary=17.73 cfs 91,231 cf
Link POA-2: North Main Street (Offsite)	Inflow=3.63 cfs 10,777 cf Primary=3.63 cfs 10,777 cf
Link POA-3: 33 N Main Street (Offsite)	Inflow=1.32 cfs 4,060 cf Primary=1.32 cfs 4,060 cf

Total Runoff Area = 357,912 sf Runoff Volume = 138,239 cf Average Runoff Depth = 4.63"
67.10% Pervious = 240,161 sf 32.90% Impervious = 117,751 sf

Summary for Subcatchment 1S: Proposed WS-1A


Runoff = 19.31 cfs @ 12.09 hrs, Volume= 58,581 cf, Depth> 5.50"
 Routed to Pond UDS-1 : Cultec 330 XLHD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description
2,745	98	Unconnected pavement, HSG A
33,953	98	Unconnected pavement, HSG B
21,986	98	Unconnected pavement, HSG C
1,946	39	>75% Grass cover, Good, HSG A
41,046	61	>75% Grass cover, Good, HSG B
26,087	74	>75% Grass cover, Good, HSG C
127,763	80	Weighted Average
69,079		54.07% Pervious Area
58,684		45.93% Impervious Area
58,684		100.00% Unconnected

Tc	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 1S: Proposed WS-1A




Summary for Subcatchment 7S: Proposed WS-1B

Runoff = 2.62 cfs @ 12.09 hrs, Volume= 7,704 cf, Depth> 3.68"
Routed to Pond RG-1 : Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description
10,733	98	Unconnected pavement, HSG A
0	98	Unconnected pavement, HSG B
0	98	Unconnected pavement, HSG C
14,409	39	>75% Grass cover, Good, HSG A
0	61	>75% Grass cover, Good, HSG B
0	74	>75% Grass cover, Good, HSG C
25,142	64	Weighted Average
14,409		57.31% Pervious Area
10,733		42.69% Impervious Area
10,733		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 7S: Proposed WS-1B

23048_Post-Dev

Prepared by Highpoint Engineering, Inc

HydroCAD® 10.20-5c s/n 08358 © 2023 HydroCAD Software Solutions LLC

Proposed Condition

Type III 24-hr 100-YR Rainfall=8.23"

Printed 12/6/2024

Page 73

Summary for Subcatchment 8S: Proposed WS-1C


Runoff = 2.43 cfs @ 12.56 hrs, Volume= 13,952 cf, Depth> 2.66"
Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Adj	Description
0	98		Unconnected pavement, HSG A
3,231	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
18,478	39		>75% Grass cover, Good, HSG A
41,290	61		>75% Grass cover, Good, HSG B
0	74		>75% Grass cover, Good, HSG C
62,999	56	55	Weighted Average, UI Adjusted
59,768			94.87% Pervious Area
3,231			5.13% Impervious Area
3,231			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
10.6	50	0.0100	0.08
27.2	920	0.0065	0.56
37.8	970	Total	

Sheet Flow,
Grass: Dense n= 0.240 P2= 3.35"
Shallow Concentrated Flow,
Short Grass Pasture Kv= 7.0 fps

Subcatchment 8S: Proposed WS-1C




Summary for Subcatchment 10S: Proposed WS-3

Runoff = 3.63 cfs @ 12.09 hrs, Volume= 10,777 cf, Depth> 4.69"
 Routed to Link POA-2 : North Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Adj	Description
38	98		Unconnected pavement, HSG A
1,589	98		Unconnected pavement, HSG B
0	98		Unconnected pavement, HSG C
1,223	39		>75% Grass cover, Good, HSG A
0	61		>75% Grass cover, Good, HSG B
24,702	74		>75% Grass cover, Good, HSG C
27,552	74	73	Weighted Average, UI Adjusted
25,925			94.09% Pervious Area
1,627			5.91% Impervious Area
1,627			100.00% Unconnected
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)
Capacity (cfs)			Description
6.0			Direct Entry,

Subcatchment 10S: Proposed WS-3



Summary for Subcatchment 11S: Proposed WS-4


Runoff = 1.32 cfs @ 12.11 hrs, Volume= 4,060 cf, Depth> 2.38"
 Routed to Link POA-3 : 33 N Main Street (Offsite)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description			
0	98	Unconnected pavement, HSG A			
0	98	Unconnected pavement, HSG B			
0	98	Unconnected pavement, HSG C			
8,496	39	>75% Grass cover, Good, HSG A			
11,996	61	>75% Grass cover, Good, HSG B			
0	74	>75% Grass cover, Good, HSG C			
20,492	52	Weighted Average			
20,492		100.00% Pervious Area			
Tc	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.9	50	0.0700	0.17		Sheet Flow, Grass: Dense n= 0.240 P2= 3.35"
1.5	145	0.0520	1.60		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
6.4	195				Total

Subcatchment 11S: Proposed WS-4

Hydrograph



Summary for Subcatchment 17S: Proposed WS-1D


Runoff = 8.68 cfs @ 12.09 hrs, Volume= 26,720 cf, Depth> 5.85"
 Routed to Pond DB-1 : Det Basin

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description
0	98	Unconnected pavement, HSG A
17,482	98	Unconnected pavement, HSG B
11,314	98	Unconnected pavement, HSG C
0	39	>75% Grass cover, Good, HSG A
13,949	61	>75% Grass cover, Good, HSG B
12,052	74	>75% Grass cover, Good, HSG C
54,797	83	Weighted Average
26,001		47.45% Pervious Area
28,796		52.55% Impervious Area
28,796		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Subcatchment 17S: Proposed WS-1D




Summary for Subcatchment 23S: Proposed WS-1E

Runoff = 5.50 cfs @ 12.09 hrs, Volume= 16,446 cf, Depth> 5.04"
 Routed to Link POA-1 : Hunting Lane (Off-site)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type III 24-hr 100-YR Rainfall=8.23"

Area (sf)	CN	Description		
0	98	Unconnected pavement, HSG A		
14,680	98	Unconnected pavement, HSG B		
0	98	Unconnected pavement, HSG C		
0	39	>75% Grass cover, Good, HSG A		
21,286	61	>75% Grass cover, Good, HSG B		
3,201	74	>75% Grass cover, Good, HSG C		
39,167	76	Weighted Average		
24,487		62.52% Pervious Area		
14,680		37.48% Impervious Area		
14,680		100.00% Unconnected		
Tc	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
6.0				Direct Entry,

Subcatchment 23S: Proposed WS-1E



Summary for Pond DB-1: Det Basin

Inflow Area = 54,797 sf, 52.55% Impervious, Inflow Depth > 5.85" for 100-YR event
 Inflow = 8.68 cfs @ 12.09 hrs, Volume= 26,720 cf
 Outflow = 4.72 cfs @ 12.22 hrs, Volume= 22,659 cf, Atten= 46%, Lag= 8.0 min
 Primary = 4.72 cfs @ 12.22 hrs, Volume= 22,659 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 177.65' @ 12.22 hrs Surf.Area= 3,959 sf Storage= 7,680 cf
 Flood Elev= 178.00' Surf.Area= 4,254 sf Storage= 9,123 cf


Plug-Flow detention time= 85.7 min calculated for 22,583 cf (85% of inflow)
 Center-of-Mass det. time= 41.7 min (805.7 - 764.0)

Volume	Invert	Avail.Storage	Storage Description
#1	175.00'	9,123 cf	Basin A (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
175.00	1,904	0	0
176.00	2,630	2,267	2,267
177.00	3,414	3,022	5,289
178.00	4,254	3,834	9,123

Device	Routing	Invert	Outlet Devices
#1	Device 3	177.00'	2.0" x 2.0" Horiz. 12" x 24" grate X 10.00 columns X 5 rows C= 0.600 in 24.0" x 12.0" Grate (69% open area)
#2	Device 3	176.50'	6.0" Vert. Orifice/Grate X 3.00 C= 0.600 Limited to weir flow at low heads
#3	Primary	174.65'	12.0" Round HDPE Culvert L= 118.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 174.65' / 171.11' S= 0.0300 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=4.71 cfs @ 12.22 hrs HW=177.64' TW=0.00' (Dynamic Tailwater)

↑ 3=HDPE Culvert (Inlet Controls 4.71 cfs @ 6.00 fps)
 └─1=12" x 24" grate (Passes < 5.35 cfs potential flow)
 └─2=Orifice/Grate (Passes < 2.68 cfs potential flow)

Pond DB-1: Det Basin**Hydrograph**

Summary for Pond IB-1: Infil Basin

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 4.55" for 100-YR event
 Inflow = 12.26 cfs @ 12.14 hrs, Volume= 48,465 cf
 Outflow = 8.40 cfs @ 12.29 hrs, Volume= 38,361 cf, Atten= 31%, Lag= 8.5 min
 Discarded = 0.14 cfs @ 12.29 hrs, Volume= 4,532 cf
 Primary = 8.26 cfs @ 12.29 hrs, Volume= 33,828 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)
 Secondary = 0.00 cfs @ 5.00 hrs, Volume= 0 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 173.75' @ 12.29 hrs Surf.Area= 5,989 sf Storage= 13,887 cf
 Flood Elev= 175.00' Surf.Area= 7,711 sf Storage= 22,476 cf

Plug-Flow detention time= 95.2 min calculated for 38,233 cf (79% of inflow)
 Center-of-Mass det. time= 39.7 min (834.2 - 794.5)

Volume	Invert	Avail.Storage	Storage Description
#1	170.00'	22,476 cf	Basin A (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
170.00	1,749	0	0
171.00	2,649	2,199	2,199
172.00	3,770	3,210	5,409
173.00	5,000	4,385	9,794
174.00	6,327	5,664	15,457
175.00	7,711	7,019	22,476
Device	Routing	Invert	Outlet Devices
#1	Discarded	170.00'	1.020 in/hr Exfiltration over Surface area
#2	Primary	170.00'	18.0" Round Culvert L= 45.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 170.00' / 169.10' S= 0.0200 '/' Cc= 0.900 n= 0.010 PVC, smooth interior, Flow Area= 1.77 sf
#3	Device 2	173.75'	2.0" x 2.0" Horiz. Orifice/Grate X 20.00 columns X 10 rows C= 0.600 in 48.0" x 24.0" Grate (69% open area)
#4	Device 2	173.00'	48.0" W x 9.0" H Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads
#5	Secondary	174.00'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Discarded OutFlow Max=0.14 cfs @ 12.29 hrs HW=173.74' (Free Discharge)

↑ 1=Exfiltration (Exfiltration Controls 0.14 cfs)

Primary OutFlow Max=8.24 cfs @ 12.29 hrs HW=173.74' TW=0.00' (Dynamic Tailwater)

↑ 2=Culvert (Passes 8.24 cfs of 11.62 cfs potential flow)

↑ 3=Orifice/Grate (Controls 0.00 cfs)


↑ 4=Orifice/Grate (Orifice Controls 8.24 cfs @ 2.77 fps)

Secondary OutFlow Max=0.00 cfs @ 5.00 hrs HW=170.00' TW=0.00' (Dynamic Tailwater)

↑ 5=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond IB-1: Infil Basin

Hydrograph



Summary for Pond RG-1: Rain Garden

Inflow Area = 25,142 sf, 42.69% Impervious, Inflow Depth > 3.68" for 100-YR event
 Inflow = 2.62 cfs @ 12.09 hrs, Volume= 7,704 cf
 Outflow = 1.07 cfs @ 12.37 hrs, Volume= 4,346 cf, Atten= 59%, Lag= 16.7 min
 Primary = 1.07 cfs @ 12.37 hrs, Volume= 4,346 cf
 Routed to Link POA-1 : Hunting Lane (Off-site)


Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 172.31' @ 12.37 hrs Surf.Area= 3,609 sf Storage= 3,544 cf

Plug-Flow detention time= 150.3 min calculated for 4,346 cf (56% of inflow)
 Center-of-Mass det. time= 70.4 min (868.9 - 798.5)

Volume	Invert	Avail.Storage	Storage Description	
#1	171.00'	4,257 cf	Custom Stage Data (Prismatic)	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	
171.00	1,856	0	0	
172.00	3,140	2,498	2,498	
172.50	3,897	1,759	4,257	

Device	Routing	Invert	Outlet Devices
#1	Primary	172.25'	30.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=1.02 cfs @ 12.37 hrs HW=172.31' TW=0.00' (Dynamic Tailwater)
 ↑ 1=Broad-Crested Rectangular Weir (Weir Controls 1.02 cfs @ 0.59 fps)

Pond RG-1: Rain Garden

Summary for Pond UDS-1: Cultec 330 XLHD

Inflow Area = 127,763 sf, 45.93% Impervious, Inflow Depth > 5.50" for 100-YR event
 Inflow = 19.31 cfs @ 12.09 hrs, Volume= 58,581 cf
 Outflow = 12.26 cfs @ 12.14 hrs, Volume= 48,465 cf, Atten= 37%, Lag= 3.3 min
 Primary = 12.26 cfs @ 12.14 hrs, Volume= 48,465 cf
 Routed to Pond IB-1 : Infil Basin

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 173.93' @ 12.30 hrs Surf.Area= 0.142 ac Storage= 0.289 af
 Flood Elev= 174.00' Surf.Area= 0.142 ac Storage= 0.293 af

Plug-Flow detention time= 71.7 min calculated for 48,304 cf (82% of inflow)
 Center-of-Mass det. time= 24.2 min (794.5 - 770.2)

Volume	Invert	Avail.Storage	Storage Description
#1A	171.00'	0.060 af	35.33'W x 115.50'L x 3.04'H Field A 0.285 af Overall - 0.136 af Embedded = 0.149 af x 40.0% Voids
#2A	171.00'	0.136 af	Cultec R-330XLHD x 112 Inside #1 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
#3B	171.00'	0.031 af	35.33'W x 59.50'L x 3.04'H Field B 0.147 af Overall - 0.069 af Embedded = 0.078 af x 40.0% Voids
#4B	171.00'	0.069 af	Cultec R-330XLHD x 56 Inside #3 Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap Row Length Adjustment= +1.50' x 7.45 sf x 7 rows
		0.296 af	Total Available Storage

Storage Group A created with Chamber Wizard

Storage Group B created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	171.00'	15.0" Round Culvert X 4.00 L= 15.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 171.00' / 171.00' S= 0.0000 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=7.27 cfs @ 12.14 hrs HW=173.66' TW=173.51' (Dynamic Tailwater)
 ↑=Culvert (Inlet Controls 7.27 cfs @ 1.48 fps)

Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field A**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

16 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 113.50' Row Length +12.0" End Stone x 2 = 115.50' Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

112 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 5,919.8 cf Chamber Storage

12,413.0 cf Field - 5,919.8 cf Chambers = 6,493.2 cf Stone x 40.0% Voids = 2,597.3 cf Stone Storage

Chamber Storage + Stone Storage = 8,517.1 cf = 0.196 af


Overall Storage Efficiency = 68.6%

Overall System Size = 115.50' x 35.33' x 3.04'

112 Chambers

459.7 cy Field

240.5 cy Stone



Pond UDS-1: Cultec 330 XLHD - Chamber Wizard Field B**Chamber Model = Cultec R-330XLHD (Discontinued, not for new designs)**

Effective Size= 47.8"W x 30.0"H => 7.45 sf x 7.00'L = 52.2 cf

Overall Size= 52.0"W x 30.5"H x 8.50'L with 1.50' Overlap

Row Length Adjustment= +1.50' x 7.45 sf x 7 rows

52.0" Wide + 6.0" Spacing = 58.0" C-C Row Spacing

8 Chambers/Row x 7.00' Long +1.50' Row Adjustment = 57.50' Row Length +12.0" End Stone x 2 = 59.50'

Base Length

7 Rows x 52.0" Wide + 6.0" Spacing x 6 + 12.0" Side Stone x 2 = 35.33' Base Width

30.5" Chamber Height + 6.0" Stone Cover = 3.04' Field Height

56 Chambers x 52.2 cf +1.50' Row Adjustment x 7.45 sf x 7 Rows = 2,999.0 cf Chamber Storage

6,394.6 cf Field - 2,999.0 cf Chambers = 3,395.6 cf Stone x 40.0% Voids = 1,358.2 cf Stone Storage

Chamber Storage + Stone Storage = 4,357.3 cf = 0.100 af


Overall Storage Efficiency = 68.1%

Overall System Size = 59.50' x 35.33' x 3.04'


56 Chambers

236.8 cy Field

125.8 cy Stone



Pond UDS-1: Cultec 330 XLHD




Summary for Link POA-1: Hunting Lane (Off-site)

Inflow Area = 309,868 sf, 37.48% Impervious, Inflow Depth > 3.53" for 100-YR event

Inflow = 17.73 cfs @ 12.33 hrs, Volume= 91,231 cf

Primary = 17.73 cfs @ 12.33 hrs, Volume= 91,231 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-1: Hunting Lane (Off-site)


Summary for Link POA-2: North Main Street (Offsite)

Inflow Area = 27,552 sf, 5.91% Impervious, Inflow Depth > 4.69" for 100-YR event

Inflow = 3.63 cfs @ 12.09 hrs, Volume= 10,777 cf

Primary = 3.63 cfs @ 12.09 hrs, Volume= 10,777 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-2: North Main Street (Offsite)


Summary for Link POA-3: 33 N Main Street (Offsite)

Inflow Area = 20,492 sf, 0.00% Impervious, Inflow Depth > 2.38" for 100-YR event

Inflow = 1.32 cfs @ 12.11 hrs, Volume= 4,060 cf

Primary = 1.32 cfs @ 12.11 hrs, Volume= 4,060 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Link POA-3: 33 N Main Street (Offsite)

Stage-Area-Storage for Pond IB-1: Infil Basin

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)	Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
170.00	1,749	0	172.60	4,508	7,892
170.05	1,794	89	172.65	4,570	8,119
170.10	1,839	179	172.70	4,631	8,349
170.15	1,884	272	172.75	4,693	8,582
170.20	1,929	368	172.80	4,754	8,818
170.25	1,974	465	172.85	4,815	9,057
170.30	2,019	565	172.90	4,877	9,300
170.35	2,064	667	172.95	4,938	9,545
170.40	2,109	772	173.00	5,000	9,794
170.45	2,154	878	173.05	5,066	10,045
170.50	2,199	987	173.10	5,133	10,300
170.55	2,244	1,098	173.15	5,199	10,558
170.60	2,289	1,211	173.20	5,265	10,820
170.65	2,334	1,327	173.25	5,332	11,085
170.70	2,379	1,445	173.30	5,398	11,353
170.75	2,424	1,565	173.35	5,464	11,625
170.80	2,469	1,687	173.40	5,531	11,900
170.85	2,514	1,812	173.45	5,597	12,178
170.90	2,559	1,939	173.50	5,664	12,459
170.95	2,604	2,068	173.55	5,730	12,744
171.00	2,649	2,199	173.60	5,796	13,032
171.05	2,705	2,333	173.65	5,863	13,324
171.10	2,761	2,470	173.70	5,929	13,619
171.15	2,817	2,609	173.75	5,995	13,917
171.20	2,873	2,751	173.80	6,062	14,218
171.25	2,929	2,896	173.85	6,128	14,523
171.30	2,985	3,044	173.90	6,194	14,831
171.35	3,041	3,195	173.95	6,261	15,142
171.40	3,097	3,348	174.00	6,327	15,457
171.45	3,153	3,505	174.05	6,396	15,775
171.50	3,210	3,664	174.10	6,465	16,097
171.55	3,266	3,826	174.15	6,535	16,422
171.60	3,322	3,990	174.20	6,604	16,750
171.65	3,378	4,158	174.25	6,673	17,082
171.70	3,434	4,328	174.30	6,742	17,417
171.75	3,490	4,501	174.35	6,811	17,756
171.80	3,546	4,677	174.40	6,881	18,099
171.85	3,602	4,856	174.45	6,950	18,444
171.90	3,658	5,037	174.50	7,019	18,794
171.95	3,714	5,221	174.55	7,088	19,146
172.00	3,770	5,409	174.60	7,157	19,502
172.05	3,832	5,599	174.65	7,227	19,862
172.10	3,893	5,792	174.70	7,296	20,225
172.15	3,955	5,988	174.75	7,365	20,592
172.20	4,016	6,187	174.80	7,434	20,961
172.25	4,078	6,389	174.85	7,503	21,335
172.30	4,139	6,595	174.90	7,573	21,712
172.35	4,200	6,803	174.95	7,642	22,092
172.40	4,262	7,015	175.00	7,711	22,476
172.45	4,323	7,230			
172.50	4,385	7,447			
172.55	4,447	7,668			


lowest orifice

APPENDIX C – SUPPORTING INFORMATION

PROPOSED MULTI-FAMILY RESIDENTIAL DEVELOPMENT

41 NORTH MAIN STREET
SHERBORN, MA, 01770

OWNER/APPLICANT: BARKSY ESTATE REALTY TRUST





RENT:
ARKSY ESTATE REALTY TRUST
3 HUNTING LANE
HERBORN, MA 01770
C/O GARY LYBARSKY

CONSULTANT:

AL

PROPOSED MULTI-FAMILY RESIDENTIAL DEVELOPMENT

41 NORTH MAIN STREET
SHERBORN, MA, 01770

11 of 11

12/06/2024	PER ZBA COMMENTS	
V	DATE	DESCRIPTION

SUE TYPE:

ISSUED TO ZBA

ISSUE DATE:

PROJECT NUMBER:
23048

RAWN BY: DTR (MILL)

SEARCHED BY: DTB

Copyright (c) by Highpoint Engineering, Inc.
All Rights Reserved.

MEET TITLE

DRAFT GRADING PLAN

EET NUMBER: **EXHIBIT 2**

SUED FOR: ZBA

